

VULCANO PU HD 12 ET

Codice/Part number	Øint. / ins.Ø	spessore min/ min wall thickness	Peso/Weight	Depres./Vacuum	Curvatura/ Bending rad.	Lungh.rotolo Coil Lgth.	Volume	Fascetta doppioponte W2 double bridge W2
	[mm]	[mm]	[g/m]	[m H2O]	[mm]	[m]	[m³]	
VO 01 038.0 000.0	38*	1,20	385	6,0	40	20	0,074	-
VO 01 040.0 000.0	40*	1,20	400	6,0	50	20	0,077	-
VO 01 045.0 000.0	45*	1,20	445	6,0	50	20	0,090	-
VO 01 050.0 000.0	50	1,20	490	5,0	60	20	0,099	-
VO 01 051.0 000.0	51	1,20	500	5,0	60	20	0,106	-
VO 01 060.0 000.0	60*	1,20	635	4,5	70	20	0,122	-
VO 01 063.0 000.0	63	1,20	665	4,5	70	20	0,148	-
VO 01 065.0 000.0	65*	1,20	685	4,5	70	20	0,152	-
VO 01 070.0 000.0	70	1,20	840	4,5	80	20	0,165	-
VO 01 076.0 000.0	76	1,20	905	4,0	90	20	0,232	F2 W2 076.0 090.0
VO 01 080.0 000.0	80	1,20	950	3,5	90	20	0,254	
VO 01 090.0 000.0	90	1,20	1065	3,0	100	20	0,294	F2 W2 100.0 127.0
VO 01 100.0 000.0	100*	1,20	1180	2,5	120	15	0,281	
VO 01 102.0 000.0	102	1,20	1200	2,5	120	15	0,286	
VO 01 110.0 000.0	110	1,20	1410	2,5	130	15	0,307	
VO 01 120.0 000.0	120*	1,20	1535	2,0	140	15	0,333	F2 W2 130.0 190.0
VO 01 127.0 000.0	127	1,20	1630	2,0	150	15	0,405	
VO 01 130.0 000.0	130*	1,20	1670	2,0	150	15	0,414	
VO 01 140.0 000.0	140*	1,20	1795	1,5	160	15	0,504	
VO 01 150.0 000.0	150*	1,20	1915	1,5	170	15	0,537	F2 W2 200.0 230.0
VO 01 152.0 000.0	152	1,20	1940	1,5	170	15	0,544	
VO 01 160.0 000.0	160*	1,20	2040	1,5	180	15	0,662	
VO 01 180.0 000.0	180*	1,20	2145	1,0	210	15	0,855	
VO 01 200.0 000.0	200*	1,20	2375	1,0	230	15	1,130	F2 W2 250.0 330.0
VO 01 203.0 000.0	203*	1,20	2410	0,5	230	15	1,146	
VO 01 205.0 000.0	205*	1,20	2435	0,5	230	15	1,157	
VO 01 220.0 000.0	220*	1,20	2605	0,5	260	10	0,902	
VO 01 228.0 000.0	228*	1,20	2700	0,5	260	10	0,933	F2 W2 250.0 330.0
VO 01 250.0 000.0	250*	1,20	2955	0,5	290	10	1,170	
VO 01 254.0 000.0	254*	1,20	3000	0,5	290	10	1,188	
VO 01 279.0 000.0	279*	1,20	3555	0,5	320	10	1,301	
VO 01 305.0 000.0	305*	1,20	3880	0,5	350	10	1,613	

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

*Available on request, contact our sales office for more info and quantities