

VULCANO PU HDS 15 ET

Codice/Part number	Øint. / ins.Ø	spessore min/ min wall thickness	Peso/Weight	Depres./Vacuum	Curvatura/ Bending rad.	Lungh.rotolo Coil Lgth.	Volume	Fascetta doppioponte W2 double bridge W2
	[mm]	[mm]	[g/m]	[m H2O]	[mm]	[m]	[m³]	
VI 01 020.0 000.0	20*	1,50	250	9,5	25	20	0,037	-
VI 01 025.0 000.0	25*	1,50	300	9,5	30	20	0,044	-
VI 01 030.0 000.0	30*	1,50	395	9,5	35	20	0,054	-
VI 01 032.0 000.0	32*	1,50	420	9,5	35	20	0,060	-
VI 01 035.0 000.0	35*	1,50	455	9,5	40	20	0,065	-
VI 01 038.0 000.0	38	1,50	460	9,5	40	20	0,080	-
VI 01 040.0 000.0	40	1,50	485	9,5	50	20	0,083	-
VI 01 045.0 000.0	45*	1,50	540	9,0	50	20	0,096	-
VI 01 050.0 000.0	50	1,50	590	9,0	60	20	0,105	-
VI 01 051.0 000.0	51	1,50	605	9,0	60	20	0,112	-
VI 01 060.0 000.0	60	1,50	700	8,5	70	20	0,128	-
VI 01 063.0 000.0	63	1,50	735	8,0	70	20	0,155	-
VI 01 065.0 000.0	65*	1,50	755	7,5	70	20	0,160	-
VI 01 070.0 000.0	70	1,50	920	7,5	80	20	0,174	-
VI 01 076.0 000.0	76	1,50	995	7,0	90	20	0,243	F2 W2 076.0 090.0
VI 01 080.0 000.0	80	1,50	1045	6,0	90	20	0,265	
VI 01 090.0 000.0	90	1,50	1165	5,0	100	20	0,306	
VI 01 100.0 000.0	100*	1,50	1290	4,0	120	15	0,291	F2 W2 100.0 127.0
VI 01 102.0 000.0	102	1,50	1315	3,5	120	15	0,296	
VI 01 110.0 000.0	110	1,50	1410	3,2	130	15	0,317	
VI 01 120.0 000.0	120	1,50	1535	3,0	140	15	0,343	
VI 01 127.0 000.0	127	1,50	1935	2,9	150	15	0,419	
VI 01 130.0 000.0	130*	1,50	1975	2,6	150	15	0,428	F2 W2 130.0 190.0
VI 01 140.0 000.0	140*	1,50	2120	2,4	160	15	0,520	
VI 01 150.0 000.0	150	1,50	2265	2,0	170	15	0,554	
VI 01 152.0 000.0	152	1,50	2295	2,0	170	15	0,560	
VI 01 160.0 000.0	160	1,50	2410	1,8	180	15	0,681	
VI 01 180.0 000.0	180	1,50	2565	1,5	210	15	0,879	
VI 01 200.0 000.0	200	1,50	2840	1,2	230	15	1,159	F2 W2 200.0 230.0
VI 01 203.0 000.0	203	1,50	2880	1,2	230	15	1,175	
VI 01 220.0 000.0	220*	1,50	3115	1,0	260	10	0,923	
VI 01 228.0 000.0	228*	1,50	3225	1,0	260	10	0,954	
VI 01 250.0 000.0	250*	1,50	3525	0,8	290	10	1,194	F2 W2 250.0 330.0
VI 01 254.0 000.0	254*	1,50	3580	0,8	290	10	1,212	
VI 01 279.0 000.0	279*	1,50	3920	0,7	320	10	1,325	
VI 01 305.0 000.0	305*	1,50	5145	0,5	350	Pezz. a richiesta(max 10 m) pezzi dritti On request (max 10 m)straight pieces		
VI 01 400.0 000.0	400*	1,50	6700	0,3	480	Pezz. a richiesta(max 6 m) pezzi dritti On request (max 6 m)straight pieces		F2 W2 350.0 410.0
VI 01 500.0 000.0	500*	1,50	8355	0,2	600	6	1,612	-

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

\*Available on request,contact our sales office for more info and quantities