

# APOLLO SUPERFLEX (Cod. AS)



+50°C

-40°C



**Tubo in PVC/NBR di colore nero, rinforzato con spirale in PVC rigido antiurto.** Speciale formulazione specifica per climi molto rigidi che lo rende migliore dei prodotti analoghi in PVC comunemente impiegati. Versione antistatica con cordicella di rame disponibile su richiesta.


- Spurghi, aspirazione e mandata di liquidi, impiegato su carribotte.

*Black PVC/NBR hose, reinforced with an anti-shock rigid PVC spiral. Special formulation conceived for keeping the flexibility at extreme temperatures, better than similar PVC hoses commonly used. Antistatic version with copper wire available on request.*

- Waste Management: suction and discharge of liquids; usually used on tank trunks.

Spirale in PVC rigido antiurto  
Anti-shock rigid PVC spiral

Tubo in PVC/NBR / PVC/NBR hose



## Scheda tecnica / Technical data

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H <sub>2</sub> O	mm	m
AS01020000000	20*	3,2	3,6	300	5,0	15	8	80	50
AS01025000000	25	3,4	3,9	400	5,0	15	8	80	50
AS01030000000	30*	3,9	4,3	550	5,0	15	8	100	50
AS01032000000	31,8/1.1/4"	3,9	4,3	580	5,0	15	8	105	50
AS01035000000	35*	3,9	4,4	630	4,3	13	8	115	50
AS01038000000	38,1/1.1/2"	3,9	4,4	680	4,3	13	8	125	50
AS01040000000	40*	3,9	4,4	710	4,0	12	8	130	50
AS01045000000	45*	4,1	4,6	840	4,0	12	8	145	50
AS01050000000	50*	4,3	4,8	960	3,3	10	8	160	50
AS01051500000	51,5*	4,3	4,8	990	3,3	10	7	160	50
AS01052000000	50,8/2"	4,3	4,8	980	3,3	10	7	160	50
AS01055000000	55*	4,4	5,0	1090	3,3	10	7	180	50
AS01057000000	57*	4,4	5,0	1130	3,3	10	7	190	50
AS01060000000	60*	4,5	5,1	1220	3,3	10	7	195	50
AS01063000000	63,5/2.1/2"	4,8	5,4	1380	3,3	10	7	210	50
AS01065000000	65*	4,9	5,6	1460	3,0	9	7	210	50
AS01070000000	70*/2.3/4"	5,0	5,8	1570	3,0	9	7	225	50
AS01075000000	75*	5,0	6,1	1740	3,0	9	7	250	50
AS01076000000	76,2/3"	5,0	6,1	1760	3,0	9	7	250	50
AS01080000000	80*	5,1	6,3	1880	2,7	8	7	260	50
AS01090000000	90*	5,3	6,6	2210	2,5	7,5	7	300	30
AS01100000000	100*	6,1	7,6	2840	2,2	6,5	7	330	30
AS01102000000	102/4"	6,1	7,6	2890	2,2	6,5	6	335	30
AS01105000000	105*	6,1	7,7	3000	2,0	6	6	350	30
AS01110000000	110*	6,1	7,7	3110	2,0	6	6	360	30
AS01120000000	120*	6,3	7,9	3490	1,8	5,5	6	390	30
AS01127000000	127/5"	6,3	7,9	3680	1,8	5,5	6	410	30
AS01130000000	130*	7,0	8,3	4120	1,8	5,5	6	420	30
AS01150000000	151,5*	7,4	8,8	5030	1,5	4,5	6	500	20
AS01152000000	152,4/6"	7,4	8,8	5060	1,5	4,5	6	500	20
AS01160000000	160*	7,9	9,3	5550	1,5	4,5	6	540	20
AS01200000000	200*	11,0	12,3	9750	1,2	3,5	5	700	10
AS01203000000	203,2*/8"	11,0	12,3	9900	1,2	3,5	5	700	10

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / \*Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity