

Codice/Part number	Ø int. / ins.Ø	Spess.min/ min wall thick.	Spess.max/ max wall thick	Peso/W eight	PE/WP	PS/BP	Depr./ Vac.	R.curvatura/ Bending R.	Lg. Rotolo/ Coil Lgth.	Vol.
	[mm]	[mm]	[mm]	[g/m]	bar	bar	[m H ₂ O]	[mm]	[m]	[m ³]
XL 01 019.0 000.0	19,1*	2,2	2,9	200	5,0	15	6	200	50	0,046
XL 01 020.0 000.0	20	2,2	2,9	210	5,0	15	6	210	50	0,048
XL 01 025.0 000.0	25	2,3	3,0	270	5,0	15	6	270	50	0,078
XL 01 030.0 000.0	30	2,3	3,1	330	5,0	15	6	330	50	0,116
XL 01 032.0 000.0	31,8	2,4	3,2	360	5,0	15	6	360	50	0,122
XL 01 035.0 000.0	35*	2,5	3,3	410	5,0	15	6	410	50	0,133
XL 01 038.0 000.0	38,1	2,6	3,4	460	5,0	15	6	460	50	0,172
XL 01 040.0 000.0	40	2,6	3,5	490	5,0	15	6	490	50	0,180
XL 01 045.0 000.0	45*	2,7	3,6	570	5,0	15	6	570	50	0,234
XL 01 050.0 000.0	50	3,0	3,8	710	5,0	15	6	710	50	0,251
XL 01 052.0 000.0	50,8	3,0	3,8	720	5,0	15	6	720	50	0,254
XL 01 055.0 000.0	55*	3,0	3,9	780	5,0	15	6	780	50	0,363
XL 01 060.0 000.0	60	3,0	4,0	870	5,0	15	6	870	50	0,394
XL 01 063.0 000.0	63,5	3,0	4,0	920	5,0	15	6	920	50	0,414
XL 01 065.0 000.0	65*	3,1	4,1	970	5,0	15	6	970	50	0,636
XL 01 070.0 000.0	70*	3,2	4,3	1050	4,0	12	6	1050	50	0,683
XL 01 076.0 000.0	76,2	3,3	4,4	1180	4,0	12	6	1180	50	0,738
XL 01 080.0 000.0	80	3,6	4,8	1350	4,0	12	6	1350	50	0,778
XL 01 090.0 000.0	90*	4,2	5,6	1870	3,0	9	6	1870	30	0,783
XL 01 100.0 000.0	100	4,6	6,1	2210	3,0	9	6	2210	30	0,886
XL 01 102.0 000.0	102	4,6	6,1	2250	3,0	9	6	2250	30	0,882

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

*Available on request, contact our sales office for more info and quantities