


Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo	Vol.	
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.	
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³	
XL010190000000	19,1*/3/4"	2,2	2,9	200	5,0	15	6	110	50	0,046	
XL010200000000	20	2,2	2,9	210	5,0	15	6	110	50	0,048	
XL010220000000	22*	2,3	3,0	240	5,0	15	6	130	50	0,061	
XL010250000000	25	2,3	3,0	270	5,0	15	6	140	50	0,078	
XL010255000000	25,5*	2,3	3,0	280	5,0	15	6	140	50	0,079	
XL010300000000	30	2,3	3,1	330	5,0	15	6	170	50	0,116	
XL010320000000	31,8/1.1/4"	2,4	3,2	360	5,0	15	6	180	50	0,122	
XL010325000000	32,5*	2,4	3,2	370	5,0	15	6	180	50	0,124	
XL010350000000	35*	2,5	3,3	410	5,0	15	6	195	50	0,133	
XL010380000000	38,1/1.1/2"	2,6	3,4	460	5,0	15	6	210	50	0,172	
XL010390000000	39*	2,6	3,4	470	5,0	15	6	215	50	0,176	
XL010400000000	40	2,6	3,5	490	5,0	15	6	220	50	0,180	
XL010450000000	45*	2,7	3,6	570	5,0	15	6	250	50	0,234	
XL010500000000	50	3,0	4,0	710	5,0	15	6	270	50	0,251	
XL010520000000	50,8/2"	3,0	4,0	720	5,0	15	6	270	50	0,254	
XL010550000000	55*	3,0	4,0	780	5,0	15	6	310	50	0,363	
XL010570000000	57*	3,0	4,0	800	5,0	15	6	310	50	0,374	
XL010600000000	60	3,0	4,2	870	5,0	15	6	330	50	0,394	
XL010630000000	63,5/2.1/2"	3,0	4,2	920	5,0	15	6	350	50	0,414	
XL010650000000	65*	3,1	4,3	970	5,0	15	6	360	50	0,636	
XL010700000000	70*/2.3/4"	3,2	4,5	1050	4,0	12	6	450	50	0,683	
XL010750000000	75*	3,3	4,6	1160	4,0	12	6	500	50	0,727	
XL010760000000	76,2/3"	3,3	4,6	1180	4,0	12	6	500	50	0,738	
XL010800000000	80	3,6	5,0	1350	4,0	12	6	550	50	0,778	
XL010900000000	90*	4,2	6,0	1870	3,0	9	6	630	30	0,588	
XL011000000000	100	4,6	6,4	2210	3,0	9	6	710	30	0,866	
XL011020000000	102/4"	4,6	6,4	2250	3,0	9	6	710	30	0,882	
XL011100000000	110*	5,0	6,7	2560	3,0	9	6	720	30	1,264	
XL011200000000	120*	5,0	6,8	2810	3,0	9	6	730	30	1,368	
XL011270000000	127*/5"	5,1	6,9	3030	3,0	9	6	740	30	1,442	
XL011500000000	151,5*	5,9	7,8	4160	3,0	9	6	800	20	1,337	
XL011520000000	152,4*/6"	5,9	7,8	4180	3,0	9	6	800	20	1,344	
XL012000000000	200*	6,5	10,0	6510	2,0	6	4,5	1000	10	1,760	

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity