

Codice	∅ Int.	∅ Est.	Spess. Min.	Spess. Max	Peso	P.E.	Depr.	R. Curvatura	Lg. Rotolo	Vol.	Lg. Spiralina
Code	∅ Int.	∅ Out.	Min wall th.	Max wall th.	Weight	W.P.	Vac.	Bending	Coil lgth.	Vol.	Banding lgth.
	mm/inch	mm	mm	mm	g/m	[bar]	m H <sub>2</sub> O	mm	m	m <sup>3</sup>	mm
<b>WT010380000000</b>	38,1/1.1/2"	51,5	3,0	6,7	725	10	9,5	90	30	0,134	153
<b>WT010400000000</b>	40	53,4	3,0	6,7	745	8	9,5	100	30	0,139	152
<b>WT010500000000</b>	50	65,4	3,0	7,7	1085	7	9,5	160	30	0,251	180
<b>WT010508000000</b>	50,8/2"	66,2	3,0	7,7	1100	7	9,5	160	30	0,254	180
<b>WT010600000000</b>	60	76,8	3,0	8,4	1230	7	9,5	180	30	0,332	203
<b>WT010760000000</b>	76,2/3"	95,8	3,5	9,8	1900	6	9	200	30	0,414	225
<b>WT010800000000</b>	80	100,8	3,5	10,4	2180	6	9	210	30	0,581	225
<b>WT011000000000</b>	100	120,8	3,5	10,4	2580	6	9	300	30	0,928	240
<b>WT011020000000</b>	101,6/4"	122,6	3,5	10,5	2655	6	9	300	30	0,942	240
<b>WT011270000000</b>	127/5"	152,0	5,0	12,5	3965	5	9	380	30	1,556	292,5
<b>WT011520000000</b>	152,4/6"	180,0	5,0	13,8	5225	5	8	450	20	1,440	322,5
<b>WT012030000000</b>	203,2/8"	236,0	6,0	16,4	8245	4	8	600	10	1,888	375

**\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / \*Available on request, contact our sales office for more info and quantities**

**I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity**