

EOLO SE (Cod. EE)



Tubo di colore azzurro in PVC plastificato con spirale di rinforzo in PVC rigido antiurto. Superficie interna liscia, esterna corrugata. **Flessibile soprattutto alle basse temperature**, alta resistenza meccanica. Resiste agli agenti atmosferici e a molti prodotti chimici. Su richiesta è disponibile la versione antistatica con cordicella di rame.


- Dove è richiesto un tubo molto flessibile con resistenza al vuoto, per l'industria, per aspirapolveri domestici, per ventilazione, condizionamento e per aspirazione di fumi e gas

Light blue plasticized PVC duct reinforced with rigid anti-shock PVC spiral. Inside smooth, outside corrugated. Flexible particularly at low temperatures, high mechanical resistance. It resists to atmospherical agents and to most chemicals. On request it can be manufactured in the antistatic version with copper wire.

- For industrial and domestic vacuum cleaners, aerating and conditioning plants, suction of fumes and gases.

Spirale in PVC rigido antiurto / Anti-shock rigid PVC spiral

Tubo in PVC plastificato / Plasticized PVC hose



Scheda tecnica / Technical data

| Codice | Ø Int. | Spess. Min. | Spess. Max. | Peso | Depr. | R. Curvatura | Lg. Rotolo | Vol. |
|----------------|--------------|--------------|--------------|--------|--------------------|--------------|------------|----------------|
| Code | Ø Int. | Min wall th. | Max wall th. | Weight | Vac. | Bending | Coil lgth. | Vol. |
| | mm/inch | mm | mm | g/m | m H ₂ O | mm | m | m ³ |
| EE010160000000 | 16* | 1,2 | 2,6 | 120 | 6 | 65 | 50 | 0,037 |
| EE010190000000 | 19,1*/3/4" | 1,2 | 2,6 | 130 | 6 | 65 | 50 | 0,049 |
| EE010200000000 | 20* | 1,2 | 2,6 | 140 | 6 | 80 | 50 | 0,051 |
| EE010250000000 | 25* | 1,2 | 2,6 | 170 | 6 | 100 | 50 | 0,072 |
| EE010300000000 | 30* | 1,4 | 3,0 | 250 | 6 | 110 | 50 | 0,115 |
| EE010320000000 | 31,8*/1.1/4" | 1,4 | 3,1 | 280 | 6 | 120 | 50 | 0,122 |
| EE010350000000 | 35* | 1,5 | 3,2 | 300 | 5 | 130 | 50 | 0,132 |
| EE010380000000 | 38,1*/1.1/2" | 1,5 | 3,2 | 330 | 5 | 135 | 50 | 0,142 |
| EE010390000000 | 39* | 1,5 | 3,2 | 340 | 5 | 140 | 50 | 0,145 |
| EE010400000000 | 40* | 1,5 | 3,2 | 340 | 5 | 160 | 50 | 0,178 |
| EE010450000000 | 45* | 1,6 | 3,4 | 420 | 5 | 175 | 50 | 0,199 |
| EE010500000000 | 50* | 1,6 | 3,9 | 530 | 5 | 175 | 50 | 0,250 |
| EE010515000000 | 51,5* | 1,6 | 3,9 | 540 | 5 | 180 | 50 | 0,256 |
| EE010520000000 | 50,8*/2" | 1,6 | 3,9 | 580 | 5 | 175 | 50 | 0,253 |
| EE010550000000 | 55* | 1,7 | 4,0 | 610 | 5 | 190 | 50 | 0,272 |
| EE010570000000 | 57* | 1,7 | 4,0 | 630 | 5 | 200 | 50 | 0,374 |
| EE010600000000 | 60* | 2,0 | 4,6 | 820 | 5 | 220 | 50 | 0,399 |
| EE010630000000 | 63,5*/2.1/2 | 2,0 | 4,6 | 860 | 5 | 230 | 50 | 0,419 |
| EE010650000000 | 65* | 2,0 | 4,6 | 880 | 5 | 250 | 50 | 0,427 |
| EE010700000000 | 70*/2.3/4" | 2,0 | 5,2 | 990 | 5 | 270 | 50 | 0,463 |
| EE010760000000 | 76,2*/3" | 2,0 | 5,2 | 1070 | 5 | 290 | 50 | 0,624 |
| EE010800000000 | 80* | 2,0 | 5,4 | 1120 | 5 | 350 | 30 | 0,523 |
| EE010900000000 | 90* | 2,0 | 5,4 | 1250 | 4,5 | 400 | 30 | 0,581 |
| EE011000000000 | 100* | 2,1 | 5,6 | 1400 | 4,5 | 400 | 30 | 0,641 |
| EE011020000000 | 102*/4" | 2,1 | 5,6 | 1420 | 4,5 | 430 | 30 | 0,652 |
| EE011100000000 | 110* | 2,1 | 6,2 | 1680 | 4,5 | 470 | 30 | 0,705 |
| EE011200000000 | 120* | 2,1 | 6,3 | 1860 | 4,5 | 500 | 30 | 1,018 |
| EE011270000000 | 127*/5" | 2,2 | 6,5 | 2070 | 4,5 | 510 | 30 | 1,075 |
| EE011300000000 | 130* | 2,3 | 6,8 | 2270 | 4 | 560 | 30 | 1,103 |
| EE011400000000 | 140* | 2,3 | 7,0 | 2540 | 4 | 600 | 20 | 1,183 |
| EE011500000000 | 151,5* | 2,5 | 7,3 | 2820 | 4 | 600 | 20 | 1,276 |
| EE011520000000 | 152,4*/6" | 2,5 | 7,4 | 2880 | 4 | 650 | 20 | 1,284 |
| EE011600000000 | 160* | 2,7 | 8,0 | 3090 | 3,5 | 730 | 20 | 1,408 |
| EE011800000000 | 180* | 2,7 | 8,0 | 3470 | 3,5 | 800 | 20 | 1,568 |
| EE012000000000 | 200* | 2,7 | 8,0 | 3670 | 3,5 | 800 | 20 | 1,728 |
| EE012030000000 | 203,2*/8" | 2,7 | 8,0 | 3730 | 3 | 1250 | 10 | 1,754 |
| EE012500000000 | 250* | 2,8 | 8,4 | 4890 | 7 | 1500 | 10 | 2,134 |

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity