


Codice	Ø Int.	Spess. Min.	Spess. Max.	Peso	Depr.	R. Curvatura	Lg. Rotolo	Vol.	
	Ø Int.	Min wall th.	Max wall th.	Weight	Vac.	Bending	Coil lgth.	Vol.	
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m ³	
OP010300000000	30*	0,8	3,3	260	3,5	100	30	0,070	
OP010320000000	31,8*/1.1/4"	0,8	3,3	280	3	110	30	0,074	
OP010350000000	35*	0,8	3,5	310	3	120	30	0,081	
OP010380000000	38,1/1.1/2"	0,8	3,5	330	3	130	30	0,087	
OP010390000000	39*	0,8	3,5	340	3	135	30	0,118	
OP010400000000	40	1,0	3,6	380	3	140	30	0,121	
OP010450000000	45	1,0	3,9	480	3	160	30	0,135	
OP010500000000	50*	1,0	4,3	590	3	175	30	0,169	
OP010520000000	50,8/2"	1,0	4,3	600	3	175	30	0,171	OP02
OP010600000000	60	1,0	4,3	700	3	200	30	0,296	OP02
OP010630000000	63,5/2.1/2"	1,0	4,3	730	3	230	30	0,311	
OP010650000000	65*	1,0	4,3	750	3	230	30	0,318	
OP010700000000	70/2.3/4"	1,0	4,8	820	3	250	30	0,344	
OP010760000000	76,2/3"	1,0	4,8	890	2,5	270	30	0,371	
OP010800000000	80	1,0	5,2	990	2,5	290	30	0,391	
OP010900000000	90	1,0	5,4	1170	2,5	360	30	0,581	
OP011000000000	100	1,0	5,9	1360	2,5	400	30	0,644	
OP011020000000	102/4"	1,0	5,9	1390	2,5	400	30	0,655	OP02
OP011100000000	110*	1,0	6,1	1510	2,5	440	30	0,704	
OP011200000000	120	1,0	6,1	1640	2,5	470	30	1,015	
OP011270000000	127*/5"	1,0	6,1	1730	2,5	500	30	1,069	
OP011300000000	130*	1,0	6,1	1770	2,5	520	30	1,092	
OP011400000000	140*	1,0	6,2	1950	2	570	30	1,561	
OP011500000000	151,5*	1,0	6,6	2170	2	600	20	1,265	
OP011520000000	152,4*/6"	1,0	6,6	2180	2	600	20	1,272	
OP012540000000	254*/10"	1,2	9,4	4030	1	500	10	1,397	

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity