

Codice	β Int.	Spess. Min.	Spess. Max.	Peso	Depr.	R. Curvatura	Lg. Rotolo	Vol.
Code	β Int.	Min wall th.	Max wall th.	Weight	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m ³
EE010160000000	16*	1,2	2,6	130	6	65	50	0,037
EE010190000000	19,1*/3/4"	1,2	2,6	150	6	65	50	0,049
EE010200000000	20*	1,2	2,6	150	6	80	50	0,051
EE010250000000	25*	1,2	2,6	190	6	100	50	0,072
EE010300000000	30*	1,4	3,0	270	6	110	50	0,115
EE010320000000	31,8*/1.1/4"	1,4	3,1	300	6	120	50	0,122
EE010350000000	35*	1,5	3,2	330	5	130	50	0,132
EE010380000000	38,1*/1.1/2"	1,5	3,2	360	5	135	50	0,142
EE010390000000	39*	1,5	3,2	370	5	140	50	0,145
EE010400000000	40*	1,5	3,2	380	5	160	50	0,178
EE010450000000	45*	1,6	3,4	460	5	175	50	0,199
EE010500000000	50*	1,6	3,9	570	5	175	50	0,250
EE010515000000	51,5*	1,6	3,9	580	5	180	50	0,256
EE010520000000	50,8*/2"	1,6	3,9	580	5	175	50	0,253
EE010550000000	55*	1,7	4,0	650	5	190	50	0,272
EE010570000000	57*	1,7	4,0	680	5	200	50	0,374
EE010600000000	60*	2,0	4,6	880	5	220	50	0,399
EE010630000000	63,5*/2.1/2	2,0	4,6	930	5	230	50	0,419
EE010650000000	65*	2,0	4,6	950	5	250	50	0,427
EE010700000000	70*/2.3/4"	2,0	5,2	1070	5	270	50	0,463
EE010760000000	76,2*/3"	2,0	5,2	1160	5	290	50	0,624
EE010800000000	80*	2,0	5,4	1220	5	350	30	0,523
EE010900000000	90*	2,0	5,4	1360	4,5	400	30	0,581
EE011000000000	100*	2,1	5,6	1520	4,5	400	30	0,641
EE011020000000	102*/4"	2,1	5,6	1550	4,5	430	30	0,652
EE011100000000	110*	2,1	6,2	1810	4,5	470	30	0,705
EE011200000000	120*	2,1	6,3	2000	4,5	500	30	1,018
EE011270000000	127*/5"	2,2	6,5	2220	4,5	510	30	1,075
EE011300000000	130*	2,3	6,8	2430	4	560	30	1,103
EE011400000000	140*	2,3	7,0	2700	4	600	20	1,183
EE011500000000	151,5*	2,5	7,3	3010	4	600	20	1,276
EE011520000000	152,4*/6"	2,5	7,4	3080	4	650	20	1,284
EE011600000000	160*	2,7	8,0	3320	3,5	730	20	1,408
EE011800000000	180*	2,7	8,0	3720	3,5	800	20	1,568
EE012000000000	200*	2,7	8,0	3960	3,5	800	20	1,728
EE012030000000	203,2*/8"	2,7	8,0	4020	3	1250	10	1,754
EE012500000000	250*	2,8	8,4	5260	7	1500	10	2,134
*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request,contact our sales office for more info and quantities								
I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity								