

Codice/ Part number	Øint./ ins.Ø	Spess. min / Min wall thick.	Spess. max/ Max wall thick.	Peso/ Weight	PE / WP	PS/ BP	Depres/ Vacuum	Curvatura/ Bending	Lungh.rotolo Coil Lgth.	Vol.
	[mm]	[mm]	[mm]	[g/m]	bar	bar	[m H ₂ O]	[mm]	[m]	[m ³]
UR 01 038.0 000.0	38,1*	3,9	4,6	680	5,0	15	10	155	50	0,221
UR 01 040.0 000.0	40*	3,9	4,6	710	5,0	15	10	160	50	0,246
UR 01 045.0 000.0	45*	4,0	4,7	830	4,0	12	10	180	50	0,261
UR 01 050.0 000.0	50*	4,3	5,0	980	4,0	12	9	200	50	0,264
UR 01 052.0 000.0	50,8	4,3	5,0	990	4,0	12	9	200	50	0,353
UR 01 060.0 000.0	60*	4,5	5,3	1230	4,0	12	9	240	50	0,409
UR 01 063.0 000.0	63,5*	4,7	5,5	1360	4,0	12	9	260	50	0,539
UR 01 070.0 000.0	70*	5,0	5,9	1570	3,0	9	9	280	50	0,592
UR 01 076.0 000.0	76	4,9	5,8	1690	3,0	9	9	310	50	0,677
UR 01 080.0 000.0	80*	5,1	6,0	1790	3,0	9	9	320	50	0,710
UR 01 090.0 000.0	90	5,3	6,2	2090	3,0	9	9	360	30	0,526
UR 01 100.0 000.0	100*	6,0	7,0	2650	3,0	9	8,5	410	30	0,880
UR 01 102.0 000.0	102	6,0	7,0	2700	3,0	9	8,5	410	30	0,895
UR 01 110.0 000.0	110*	6,1	7,1	2930	3,0	9	8,5	450	30	0,998
UR 01 120.0 000.0	120*	6,2	7,3	3270	2,5	7,5	8	480	30	1,082
UR 01 127.0 000.0	127*	6,3	7,4	3510	2,5	7,5	8	510	30	1,139
UR 01 152.0 000.0	152,4	6,7	8,6	4730	2,0	6	8	610	20	1,362

URANO PU

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

*Available on request, contact our sales office for more info and quantities