



Codice	Ø Int.	Spess. Min.	Spess. Max.	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo	Vol.	
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.	
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m	m ³	
UR010380000000	38,1*/1.1/2"	3,9	4,7	680	5,0	15	10	155	50	0,182	
UR010400000000	40*	3,9	4,7	710	5,0	15	10	160	50	0,221	
UR010450000000	45*	4,0	4,9	830	4,0	12	10	180	50	0,246	
UR010500000000	50*	4,3	5,2	980	4,0	12	9	200	50	0,261	
UR010520000000	50,8/2"	4,3	5,2	990	4,0	12	9	200	50	0,264	
UR010600000000	60*	4,5	5,5	1230	4,0	12	9	240	50	0,409	
UR010630000000	63,5*/2.1/2"	4,7	5,7	1360	4,0	12	9	260	50	0,539	
UR010700000000	70*	5,0	6,1	1570	3,0	9	9	280	50	0,592	
UR010760000000	76	5,0	6,1	1690	3,0	9	9	310	50	0,677	
UR010800000000	80*	5,1	6,2	1790	3,0	9	9	320	50	0,710	
UR010900000000	90	5,3	6,4	2090	3,0	9	9	360	30	0,526	
UR011000000000	100*	6,0	7,3	2650	3,0	9	8,5	410	30	0,880	
UR011020000000	102/4"	6,0	7,3	2700	3,0	9	8,5	410	30	0,895	UR02
UR011100000000	110*	6,1	7,4	2930	3,0	9	8,5	450	30	0,998	
UR011200000000	120*	6,2	7,6	3270	2,5	7,5	8	480	30	1,082	
UR011270000000	127*/5"	6,3	7,7	3510	2,5	7,5	8	510	30	1,139	
UR011500000000	151,5*	6,7	8,9	4700	2,0	6	8	610	20	1,354	
UR011520000000	152,4/6"	6,7	8,9	4730	2,0	6	8	610	20	1,362	

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity