

Codice	∅ Int.	Spess. Min.	Peso	Depr.	R. Curvatura	Lg. Rotolo	Vol.
Code	∅ Int.	Min wall th.	Weight	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	g/m	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
EC010380000000	38*	1,50	530	9,5	40	20	0,07
EC010400000000	40*	1,50	555	9,5	50	20	0,09
EC010450000000	45*	1,50	620	9,0	50	20	0,10
EC010500000000	50*	1,50	680	9,0	60	20	0,11
EC010510000000	51*	1,50	690	9,0	60	20	0,11
EC010600000000	60*	1,50	805	8,5	70	20	0,13
EC010630000000	63*	1,50	840	8,0	70	20	0,19
EC010650000000	65*	1,50	865	7,5	70	20	0,19
EC010700000000	70*/2.3/4"	1,50	1035	7,5	80	20	0,20
EC010750000000	75*	1,50	1100	7,0	80	20	0,22
EC010760000000	76*	1,50	1115	7,0	90	20	0,22
EC010800000000	80*	1,50	1170	6,0	90	20	0,23
EC010900000000	90*	1,50	1310	5,0	100	20	0,29
EC011000000000	100*	1,50	1445	4,0	120	15	0,32
EC011020000000	102*/4"	1,50	1475	3,5	120	15	0,32
EC011100000000	110*	1,50	1585	3,2	130	15	0,35
EC011520000000	152*/6"	1,50	2520	1,8	180	15	0,70
EC011600000000	160*	1,50	2645	1,8	180	15	0,74
EC012030000000	203*/8"	1,50	3170	1,2	230	15	1,10

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / \*Available on request,contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity