

VULCANO PU H 09 ESTERE

| Codice/<br>Part number | Øint./<br>ins.Ø | Spess. Min./<br>Min wall thick. | Peso /<br>Weight | Curvatura/<br>Bending rad. | Depres./<br>Vacuum   | Lungh.rotolo<br>Coil Lgth.                           | Volume            | Fascetta<br>doppio ponte W2<br>double bridge W2 |
|------------------------|-----------------|---------------------------------|------------------|----------------------------|----------------------|--|-------------------|---|
|                        | [mm]            | [mm]                            | [g/m]            | [mm]                       | [m H <sub>2</sub> O] | [m]  | [m <sup>3</sup> ] |   |
| VB 01 020.0 000.0      | 20*             | 0,9                             | 170              | 25                         | 5,0                  | 20   | 0,040             | -   |
| VB 01 025.0 000.0      | 25*             | 0,9                             | 215              | 30                         | 5,0                  | 20   | 0,040             | -   |
| VB 01 030.0 000.0      | 30*             | 0,9                             | 260              | 35                         | 5,0                  | 20   | 0,050             | -   |
| VB 01 032.0 000.0      | 32*             | 0,9                             | 280              | 35                         | 5,0                  | 20   | 0,050             | -   |
| VB 01 035.0 000.0      | 35*             | 0,9                             | 300              | 40                         | 5,0                  | 20   | 0,060             | -   |
| VB 01 038.0 000.0      | 38              | 0,90                            | 290              | 40                         | 5,0                  | 20   | 0,060             | -   |
| VB 01 040.0 000.0      | 40              | 0,90                            | 300              | 50                         | 5,0                  | 20   | 0,070             | -   |
| VB 01 045.0 000.0      | 45*             | 0,90                            | 390              | 50                         | 5,0                  | 20   | 0,090             | -   |
| VB 01 051.0 000.0      | 51              | 0,90                            | 435              | 60                         | 4,0                  | 20   | 0,100             | -   |
| VB 01 055.0 000.0      | 55*             | 0,90                            | 470              | 65                         | 3,5                  | 20   | 0,120             | -   |
| VB 01 060.0 000.0      | 60              | 0,90                            | 510              | 70                         | 3,0                  | 20   | 0,130             | -   |
| VB 01 063.0 000.0      | 63              | 0,90                            | 530              | 70                         | 3,0                  | 20   | 0,130             | -   |
| VB 01 065.0 000.0      | 65*             | 0,90                            | 545              | 70                         | 3,0                  | 20   | 0,180             | -   |
| VB 01 070.0 000.0      | 70              | 0,90                            | 675              | 80                         | 3,0                  | 20   | 0,200             | -   |
| VB 01 076.0 000.0      | 76              | 0,90                            | 730              | 90                         | 3,0                  | 20   | 0,240             | -   |
| VB 01 080.0 000.0      | 80              | 0,90                            | 765              | 90                         | 3,0                  | 20   | 0,260             | F2 W2 076.0 090.0                               |
| VB 01 090.0 000.0      | 90              | 0,90                            | 855              | 100                        | 2,5                  | 20   | 0,290             | -   |
| VB 01 102.0 000.0      | 102             | 0,90                            | 965              | 120                        | 2,0                  | 15   | 0,320             | -   |
| VB 01 110.0 000.0      | 110*            | 0,90                            | 1035             | 130                        | 2,0                  | 15   | 0,340             | -   |
| VB 01 115.0 000.0      | 115*            | 0,90                            | 1080             | 135                        | 1,5                  | 15   | 0,360             | F2 W2 100.0 127.0                               |
| VB 01 120.0 000.0      | 120             | 0,90                            | 1125             | 140                        | 1,5                  | 15   | 0,370             | -   |
| VB 01 127.0 000.0      | 127             | 0,90                            | 1370             | 150                        | 1,5                  | 15   | 0,390             | -   |
| VB 01 130.0 000.0      | 130*            | 0,90                            | 1405             | 150                        | 1,5                  | 15   | 0,400             | -   |
| VB 01 140.0 000.0      | 140             | 0,90                            | 1505             | 160                        | 1,0                  | 15   | 0,640             | -   |
| VB 01 150.0 000.0      | 150*            | 0,90                            | 1610             | 170                        | 1,0                  | 15   | 0,690             | F2 W2 130.0 190.0                               |
| VB 01 152.0 000.0      | 152             | 0,90                            | 1630             | 170                        | 1,0                  | 15   | 0,700             | -   |
| VB 01 160.0 000.0      | 160             | 0,90                            | 1715             | 180                        | 1,0                  | 15   | 0,730             | -   |
| VB 01 180.0 000.0      | 180             | 0,90                            | 1720             | 210                        | 0,5                  | 15   | 0,970             | -   |
| VB 01 200.0 000.0      | 200             | 0,90                            | 1905             | 230                        | 0,5                  | 15   | 1,080             | -   |
| VB 01 203.0 000.0      | 203             | 0,90                            | 1930             | 230                        | 0,5                  | 15   | 1,090             | F2 W2 200.0 230.0                               |
| VB 01 220.0 000.0      | 220*            | 0,90                            | 2090             | 260                        | 0,3                  | 10   | 1,180             | -   |
| VB 01 228.0 000.0      | 228*            | 0,90                            | 2160             | 260                        | 0,3                  | 10   | 1,220             | -   |
| VB 01 250.0 000.0      | 250*            | 0,90                            | 2365             | 290                        | 0,3                  | 10   | 1,330             | -   |
| VB 01 254.0 000.0      | 254             | 0,90                            | 2400             | 290                        | 0,3                  | 10   | 1,350             | -   |
| VB 01 279.0 000.0      | 279*            | 0,90                            | 2870             | 320                        | 0,2                  | 10   | 1,480             | -   |
| VB 01 300.0 000.0      | 300*            | 0,90                            | 3080             | 350                        | 0,2                  | 10   | 1,590             | F2 W2 250.0 330.0                               |
| VB 01 305.0 000.0      | 305             | 0,90                            | 3130             | 350                        | 0,2                  | 10   | 1,610             | -   |
| VB 01 315.0 000.0      | 315*            | 0,90                            | 3230             | 350                        | 0,2                  | 10   | 1,660             | -   |
| VB 01 350.0 000.0      | 350*            | 0,90                            | 4075             | 410                        | 0,1                  | Pezz. a richiesta(max 10 m)<br>On request (max 10 m) | -                 | -   |
| VB 01 356.0 000.0      | 356*            | 0,90                            | 4145             | 410                        | 0,1                  | Pezz. a richiesta(max 10 m)<br>On request (max 10 m) | -                 | F2 W2 350.0 410.0                               |

|  |                          |      |      |      |      |     |  |   |
|--|--------------------------|------|------|------|------|-----|--|---|
|  | <b>VB 01 400.0 000.0</b> | 400* | 0,90 | 4645 | N.D. | 0,1 | Pezz. a richiesta (max 10 m)<br>On request (max 10 m)                    |   |
|  | <b>VB 01 450.0 000.0</b> | 450* | 0,90 | 6535 | N.D. | 0,1 | Pezz.a richiesta(max 6 m) pz. dritti<br>On request(max 6 m)straight pcs. | - |

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

\*Available on request,contact our sales office for more info and quantities