

Codice/Part number	Øint. / ins.Ø	spess. min/ min wall thick	Peso/ Weight	Depres./ Vacuum	Curvatura/ Bending	Lungh.rotolo Coil Lgth.	Vol.	Fascetta doppioponte W2 double bridge W2
	[mm]	[mm]	[g/m]	[m H ₂ O]	[mm]	[m]	[m ³]	
VO 01 038.0 000.0	38*	1,20	385	6,0	40	20	0,070	-
VO 01 040.0 000.0	40*	1,20	405	6,0	50	20	0,090	-
VO 01 045.0 000.0	45*	1,20	450	6,0	50	20	0,100	-
VO 01 050.0 000.0	50	1,20	495	5,0	60	20	0,100	-
VO 01 051.0 000.0	51	1,20	505	5,0	60	20	0,110	-
VO 01 060.0 000.0	60*	1,20	645	4,5	70	20	0,130	-
VO 01 063.0 000.0	63	1,20	675	4,5	70	20	0,180	-
VO 01 065.0 000.0	65*	1,20	695	4,5	70	20	0,190	-
VO 01 070.0 000.0	70	1,20	845	4,5	80	20	0,200	-
VO 01 076.0 000.0	76	1,20	915	4,0	90	20	0,220	F2 W2 076.0 090.0
VO 01 080.0 000.0	80	1,20	960	3,5	90	20	0,230	
VO 01 090.0 000.0	90	1,20	1070	3,0	100	20	0,280	F2 W2 100.0 127.0
VO 01 100.0 000.0	100*	1,20	1185	2,5	120	15	0,310	
VO 01 102.0 000.0	102	1,20	1205	2,5	120	15	0,320	
VO 01 110.0 000.0	110	1,20	1420	2,5	130	15	0,340	
VO 01 120.0 000.0	120*	1,20	1545	2,0	140	15	0,370	F2 W2 130.0 190.0
VO 01 127.0 000.0	127	1,20	1635	2,0	150	15	0,390	
VO 01 130.0 000.0	130*	1,20	1670	2,0	150	15	0,400	
VO 01 140.0 000.0	140*	1,20	1795	1,5	160	15	0,640	
VO 01 150.0 000.0	150*	1,20	1920	1,5	170	15	0,690	
VO 01 152.0 000.0	152	1,20	1945	1,5	170	15	0,700	
VO 01 160.0 000.0	160*	1,20	2040	1,5	180	15	0,730	F2 W2 200.0 230.0
VO 01 180.0 000.0	180*	1,20	2060	1,0	210	15	0,970	
VO 01 200.0 000.0	200*	1,20	2285	1,0	230	15	1,080	
VO 01 203.0 000.0	203*	1,20	2320	0,5	230	15	1,090	
VO 01 205.0 000.0	205*	1,20	2340	0,5	230	15	1,100	F2 W2 250.0 330.0
VO 01 220.0 000.0	220*	1,20	2505	0,5	260	10	1,180	
VO 01 228.0 000.0	228*	1,20	2595	0,5	260	10	1,220	F2 W2 250.0 330.0
VO 01 250.0 000.0	250*	1,20	2840	0,5	290	10	1,330	
VO 01 254.0 000.0	254*	1,20	2885	0,5	290	10	1,350	
VO 01 279.0 000.0	279*	1,20	3555	0,5	320	10	1,480	F2 W2 250.0 330.0
VO 01 305.0 000.0	305*	1,20	3885	0,5	350	10	1,610	

VULCANO PU HD 12 ET

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

*Available on request, contact our sales office for more info and quantities