

Codice/ Part number	Øint./ ins.Ø	Spess. Min./ Min wall thick.	Peso/ Weight	Curvatura/ Bending rad.	Depres./ Vacuum	Lungh.rotolo/ Coil Lgth.	Volume	Fascetta doppioponte W2 double bridge W2
	[mm]	[mm]	[g/m]	[mm]	[m H ₂ O]	[m]	[m ³]	
VC 01 020.0 000.0	20*	1,50	245	25	9,5	20	0,030	-
VC 01 025.0 000.0	25*	1,50	305	30	9,5	20	0,050	-
VC 01 030.0 000.0	30*	1,50	440	35	9,5	20	0,060	-
VC 01 032.0 000.0	32*	1,50	465	35	9,5	20	0,060	-
VC 01 035.0 000.0	35*	1,50	500	40	9,5	20	0,060	-
VC 01 038.0 000.0	38	1,50	535	40	9,5	20	0,090	-
VC 01 040.0 000.0	40	1,50	560	50	9,5	20	0,090	-
VC 01 045.0 000.0	45*	1,50	620	50	9,0	20	0,100	-
VC 01 050.0 000.0	50	1,50	685	60	9,0	20	0,110	-
VC 01 051.0 000.0	51	1,50	695	60	9,0	20	0,120	-
VC 01 060.0 000.0	60	1,50	810	70	8,5	20	0,130	-
VC 01 063.0 000.0	63	1,50	845	70	8,0	20	0,190	-
VC 01 065.0 000.0	65*	1,50	870	70	7,5	20	0,190	-
VC 01 070.0 000.0	70	1,50	1005	80	7,5	20	0,200	-
VC 01 076.0 000.0	76	1,50	1090	90	7,0	20	0,250	F2 W2 076.0 090.0
VC 01 080.0 000.0	80	1,50	1140	90	6,0	20	0,260	
VC 01 090.0 000.0	90	1,50	1275	100	5,0	20	0,290	
VC 01 100.0 000.0	100*	1,50	1410	120	4,0	15	0,320	F2 W2 100.0 127.0
VC 01 102.0 000.0	102	1,50	1435	120	3,5	15	0,320	
VC 01 110.0 000.0	110*	1,50	1545	130	3,2	15	0,350	
VC 01 115.0 000.0	115*	1,50	1610	135	3,0	15	0,360	
VC 01 120.0 000.0	120	1,50	1675	140	3,0	15	0,370	
VC 01 127.0 000.0	127	1,50	2075	150	2,9	15	0,400	
VC 01 130.0 000.0	130*	1,50	2120	150	2,6	15	0,610	F2 W2 130.0 190.0
VC 01 140.0 000.0	140	1,50	2275	160	2,4	15	0,650	
VC 01 150.0 000.0	150*	1,50	2435	170	2,0	15	0,690	
VC 01 152.0 000.0	152	1,50	2465	170	2,0	15	0,700	
VC 01 160.0 000.0	160	1,50	2590	180	1,8	15	0,740	
VC 01 175.0 000.0	175*	1,50	2705	200	1,5	15	0,950	
VC 01 180.0 000.0	180	1,50	2780	210	1,5	15	0,980	F2 W2 200.0 230.0
VC 01 200.0 000.0	200*	1,50	3080	230	1,2	15	1,080	
VC 01 203.0 000.0	203	1,50	3125	230	1,2	15	1,100	
VC 01 228.0 000.0	228*	1,50	3500	260	1,0	10	1,230	F2 W2 250.0 330.0
VC 01 250.0 000.0	250*	1,50	3830	290	0,8	10	1,340	
VC 01 254.0 000.0	254	1,50	3890	290	0,8	10	1,360	
VC 01 279.0 000.0	279*	1,50	4265	320	0,7	10	1,490	
VC 01 305.0 000.0	305	1,50	5680	350	0,7	Pezz. a richiesta(max 10 m) pz.dritti / On request(max 10 m)straight pcs.		
VC 01 320.0 000.0	320*	1,50	5955	N.D.	0,7	Pezz. a richiesta(max 10 m) pz.dritti On request (max 10 m)straight pcs.		
VC 01 350.0 000.0	350*	1,50	6500	N.D.	0,7	Pezz. a richiesta(max 10 m) pz.dritti On request(max 10 m)straight pcs.	F2 W2 350.0 410.0	
VC 01 400.0 000.0	400*	1,50	7415	N.D.	0,7	Pezz. a richiesta(max 10 m) pz.dritti On request(max 10 m)straight pcs.		
VC 01 406.0 000.0	406*	1,50	7525	N.D.	0,7	Pezz. a richiesta(max 6 m dritti On request(max 6 m)straight pcs.		
VC 01 500.0 000.0	500*	1,50	9240	600	0,2	5	1,306	-

VULCANO PU HDS 15 ESTERE

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite

*Available on request,contact our sales office for more info and quantities