

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	Depr.	R. Curvatura	Lg. Rotolo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m ³
ZE010300000000	30*	1,2	3,7	320	9	130	30	0,072
ZE010320000000	31,8/1.1/4"	1,2	3,8	350	9	140	30	0,076
ZE010350000000	35*	1,3	4,0	380	9	160	30	0,083
ZE010380000000	38,1/1.1/2"	1,3	4,0	420	9	180	30	0,118
ZE010400000000	40	1,5	4,3	500	9	190	30	0,124
ZE010450000000	45*	1,5	4,4	570	8	200	30	0,172
ZE010500000000	50*	1,5	4,8	690	8	215	30	0,172
ZE010520000000	50,8/2"	1,5	4,8	700	8	215	30	0,174
ZE010550000000	55*	1,5	4,9	780	8	225	30	0,187
ZE010570000000	57*	1,5	4,9	800	8	225	30	0,192
ZE010600000000	60	1,5	5,0	870	8	230	30	0,302
ZE010630000000	63,5/2.1/2"	1,5	5,0	920	8	240	30	0,318
ZE010650000000	65*	1,5	5,0	940	8	240	30	0,324
ZE010700000000	70/2.3/4"	1,5	5,3	950	8	250	30	0,348
ZE010760000000	76,2/3"	1,7	5,5	1120	8	270	30	0,377
ZE010800000000	80	2,0	5,9	1260	7	290	30	0,397
ZE010900000000	90	2,0	5,9	1410	7	380	30	0,586
ZE011000000000	100	2,0	6,3	1600	7	420	30	0,649
ZE011020000000	102/4"	2,0	6,3	1630	7	420	30	0,660
ZE011100000000	110*	2,0	7,6	2220	6,5	450	30	0,901
ZE011200000000	120	2,0	7,6	2410	6,5	480	30	0,973
ZE011270000000	127/5"	2,0	7,6	2540	6,5	530	30	1,092
ZE011500000000	151,2	2,0	8,1	3110	6	800	20	1,286
*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request,contact our sales office for more info and quantities								
I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity								