



FICHA TÉCNICA · TECHNICAL DATA



F2 W2 p.122

Abrazaderas doble puente W2 / Double bridge W2

ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES



VULCANO STONE PLUS (cód.TH 07) p.22

CÓDIGO CODE	Ø INT.	MIN ESP.	PESO	VACIO	R. CURVATURA	LG. ROLLO	VOL.
	Ø INT. mm/inch	MIN WALL TH. mm	WEIGHT g/m	VACUUM m H ₂ O	BENDING mm	COIL LGTH. m	VOL. m ³
TH010380000000*	38	2	800	9,7	150	15	0,06
TH010400000000*	40	2	840	9,7	160	15	0,07
TH010450000000*	45	2	930	9,7	180	15	0,11
TH010510000000*	51	2	1140	9,7	204	15	0,12
TH010600000000*	60	2	1320	9,7	240	15	0,18
TH010630000000*	63	2	1380	9,7	250	15	0,19
TH010650000000*	65	2	1420	9,7	250	15	0,20
TH010700000000*	70	2	1520	9,5	280	15	0,21
TH010760000000*	76	2	1640	9,5	305	15	0,25
TH010800000000*	80	2	1720	9,5	320	15	0,26
TH010900000000*	90	2	1925	9,5	360	15	0,29
TH011000000000*	100	2	2275	9,5	400	10	0,32
TH011020000000*	102	2	2320	9,5	410	10	0,33
TH011100000000*	110	2	2490	9,4	440	10	0,35
TH011150000000*	115	2	2600	9,4	460	10	0,37
TH011200000000*	120	2	2705	9,2	480	10	0,68
TH011270000000*	127	2	2965	9	510	tramo 10 m/ straight	0,72
TH011300000000*	130	2	3030	9	520	tramo 10 m/ straight	0,73
TH011400000000*	140	2	3255	8,7	560	tramo 10 m/ straight	0,23
TH011500000000*	150	2	3475	8,5	600	tramo 10 m/ straight	0,27
TH011520000000*	152	2	3520	8,2	610	tramo 10 m/ straight	0,27
TH011600000000*	160	2	4245	8	640	tramo 10 m/ straight	0,30
TH011800000000*	180	2	4750	7	810	tramo 10 m/ straight	0,37
TH012000000000*	200	2	5260	6	1000	tramo 10 m/ straight	1,64
TH012030000000*	203	2	5335	6	1015	tramo 10 m/ straight	0,47
TH012280000000*	228	2	5975	5	-	tramo 6 m/ straight	0,35
TH012400000000*	240	2	6280	4	-	tramo 6 m/ straight	0,39
TH012450000000*	245	2	6405	4	-	tramo 6 m/ straight	0,40
TH012500000000*	250	2	6535	4	-	tramo 6 m/ straight	0,42
TH012540000000*	254	2	6635	4	-	tramo 6 m/ straight	0,43

*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.