



**ES** Tubo de PVC/NBR de color azul, reforzado con espiral de PVC rígido antichoque. Interno liso y externo ligeramente corrugado. Muy resistente al aplastamiento, a la abrasión, a los agentes atmosféricos y a numerosas substancias químicas. Versión antiestática con hilo de cobre (cód. OI 02) disponible según pedido.

• Aspiración e impulsión de aceites minerales, lubricantes, carburantes crudos (nafta, diesel) y como línea de retorno de circuitos hidráulicos.

**EN** Blue PVC-NBR hose manufactured incorporating a spiral reinforcement of anti-shock rigid PVC. Inside surface smooth, light corrugated outside. Very strong and resistant to crushing, abrasion, weathering and most chemicals. On request, It can be manufactured in the AS version with copper wire (Cod. OI 02).

• Suction and delivery of mineral oils, lubricants, crude fuel (naphta, diesel oil) and as a return line in hydraulic systems.

## CÓD. OI 01

Ø mm 20-203

Espirales de PVC rígido antichoque  
Anti-shock rigid PVC spiral



Tubo in PVC-NBR  
PVC-NBR hose




### FICHA TÉCNICA · TECHNICAL DATA

3,2-10,9

+60°C  
-25°C

### ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES



APOLLO NL1 OIL(cód. A1 09) p.61

CÓDIGO	Ø INT.	MIN ESP.	MAX ESP.	PESO	P.T.	P.R.	VACIO	R. CURVATURA	LG. ROLLO	VOLUME
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING R.	COIL LGTH.	VOLUME
	mm	mm	mm	g/m	bar	bar	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
OI01020000000*	20	3,2	3,5	290	7	21	10	80	50	0,069
OI01025000000*	25	3,4	3,8	390	6	18	10	100	50	0,083
OI01025400000*	25,4	3,4	3,8	400	6	18	10	100	50	0,084
OI01032000000*	31,8	4	4,4	590	6	18	10	130	50	0,130
OI01038000000*	38,1	3,9	4,5	670	5	15	10	155	50	0,203
OI01040000000*	40	3,9	4,5	700	5	15	10	160	50	0,212
OI01052000000*	50,8	4,3	4,9	970	4	12	10	200	50	0,262
OI01055000000*	55	4,5	5,1	1100	4	12	9	220	50	0,376
OI01060000000*	60	4,7	5,4	1270	4	12	9	260	50	0,408
OI01063000000*	63,5	4,8	5,5	1370	4	12	9	260	50	0,429
OI01070000000*	70	4,9	5,6	1490	3	9	9	350	50	0,585
OI01076000000*	76,2	5	5,7	1660	3	9	9	310	50	0,631
OI01080000000*	80	5,2	6	1810	3	9	9	400	50	0,795
OI01090000000*	90	5,4	6,3	2110	3	9	9	360	30	0,591
OI01102000000*	102	6	7,1	2680	3	9	8,5	410	30	0,837
OI01127000000*	127	6,4	7,5	3510	2,5	7,5	8	510	30	1,091
OI01152000000*	152,4	7,4	8,7	4930	2	6	8	610	20	1,358
OI01203000000*	203,2	10,9	12,9	10010	1,5	4,5	7	850	10	1,832

\*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

\*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.