


EOLO CLIP HYPALON



IT Tubo grigio scuro in tessuto di poliestere spalmato in Hypalon, rinforzato con spirale in acciaio galvanizzato clippata alla parete. Comprimibile assialmente (4:1). Tubo molto

flexibile, resistente a vibrazioni, olii minerali, alle sostanze alcaline, agli acidi e a molti prodotti chimici. Resistente allo schiacciamento. Difficilmente infiammabile.

- aspirazione di fumi e vapori chimici fino a 170 °C. Idoneo all'installazione in spazi angusti, in cui si richiedano raggi di curvatura particolarmente stretti.

EN Dark grey Hypalon® coated PES-fabric with external galvanized steel spiral.

Compressible 4:1. Very flexible, resistant to vibrations, mineral oils, chemicals (alkali and acids) and to several chemicals. Crush proof. Hardly inflammable.

- Suction and delivery of chemical vapours and fumes up to 170°C. Suitable to be installed in narrow spaces and where special bending radius is required.

COD. EY

Ø mm 50-900



Tessuto di poliestere spalmato di Hypalon
Hypalon coated PES- fabric

Spirale in acciaio
Steel spiral



SCHEMA TECNICA · TECHNICAL DATA	CODICE	Ø INT.	PESO	P.E.	DEPR	R. CURVATURA	LG. ROTOLO
	CODE	Ø INT.	WEIGHT	W.P.	VACUUM	BENDING	COIL LGTH.
		mm	g/m	Bar	m H ₂ O	mm	m
+170°C picchi peaks +190°C -40°C ARTICOLI DELLA STESSA SERIE ITEMS IN THE SAME SERIES EOLO HT 400°C (cod. H4) p.50 EOLO HT 450 °C (cod. H5) p.51	EY010500000000*	50	400	0,90	4,08	30	6
	EY010600000000*	60	500	0,78	2,83	36	6
	EY010650000000*	65	500	0,68	2,42	39	6
	EY010700000000*	70	500	0,67	2,08	42	6
	EY010750000000*	75	600	0,62	1,82	45	6
	EY010800000000*	80	600	0,61	1,59	48	6
	EY010900000000*	90	600	0,56	1,25	54	6
	EY011000000000*	100	600	0,51	1,02	60	6
	EY011100000000*	110	700	0,48	0,85	66	6
	EY011200000000*	120	700	0,36	0,71	72	6
	EY011250000000*	125	800	0,33	0,65	75	6
	EY011300000000*	130	800	0,28	0,60	78	6
	EY011400000000*	140	800	0,25	0,52	84	6
	EY011500000000*	150	900	0,22	0,45	90	6
	EY011600000000*	160	900	0,21	0,40	96	6
	EY011700000000*	170	900	0,19	0,36	102	6
	EY011750000000*	175	1000	0,19	0,34	105	6
	EY011800000000*	180	1000	0,17	0,32	108	6
	EY012000000000*	200	1200	0,15	0,25	120	6
	EY012150000000*	215	1300	0,13	0,22	129	6
	EY012250000000*	225	1400	0,12	0,20	135	6
	EY012500000000*	250	1600	0,1	0,16	175	6
	EY012750000000*	275	1900	0,08	0,13	193	6
	EY013000000000*	300	2100	0,07	0,11	210	6
	EY013150000000*	315	2100	0,06	0,10	221	6
	EY013250000000*	325	2200	0,06	0,10	228	6
	EY013500000000*	350	2500	0,06	0,08	245	6
	EY013750000000*	375	2900	0,05	0,07	263	6
	EY014000000000*	400	3100	0,05	0,06	280	6
	EY014500000000*	450	3600	0,05	0,05	360	6
	EY015000000000*	500	4100	0,04	0,04	400	6
	EY016000000000*	600	5100	0,04	0,03	480	6
	EY017000000000*	700	6000	0,03	0,02	560	6
	EY018000000000*	800	6900	0,02	0,02	640	6
	EY019000000000*	900	7800	0,02	0,01	720	6

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% humidity.