

SCHEDA TECNICA - TECHNICAL DATA




disponibile a magazzino
available on stock




+50°C

-10°C


ARTICOLI DELLA STESSA SERIE ITEMS IN THE SAME SERIES



EOLO (cod. EO) p.42



EOLO SE (cod. EE) p.43



EOLO SL (cod. ES) p.40

CODICE	Ø INT.	SPESS. MIN.	SPESS. MAX.	PESO	DEPR.	R. CURVATURA	LG. ROTOLO	VOL.
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m³
EL010250000000	25	0,8	2,7	160	2,5	30	50	0,073
EL010270000000*	27	0,8	2,7	170	2,5	30	50	0,082
EL010300000000	30	0,8	2,8	200	2,5	40	50	0,115
EL010320000000	31,8	0,8	2,8	210	2	40	50	0,121
EL010350000000	35	0,8	2,9	220	2	40	50	0,131
EL010380000000	38,1	0,8	3,1	270	2	50	50	0,142
EL010390000000*	39	0,8	3,1	270	2	50	50	0,145
EL010400000000	40	0,8	3,1	280	2	50	50	0,177
EL010450000000	45	0,8	3,4	350	2	60	50	0,199
EL010500000000	50	0,9	3,7	430	2	60	50	0,248
EL010515000000*	51,5	0,9	3,7	440	2	60	50	0,254
EL010520000000	50,8	0,9	3,7	440	2	60	50	0,251
EL010550000000*	55	0,9	3,7	470	2	70	50	0,270
EL010600000000	60	0,9	3,7	510	1,6	80	50	0,388
EL010630000000	63,5	0,9	3,7	540	1,6	80	50	0,408
EL010650000000*	65	0,9	3,7	550	1,6	80	50	0,417
EL010700000000	70	1	3,9	590	1,5	90	50	0,448
EL010750000000	75	1	4	650	1,5	90	50	0,598
EL010760000000	76,2	1	4	660	1,5	100	50	0,606
EL010777000000*	77,7	1	4	670	1,5	100	50	0,617
EL010800000000	80	1	4,6	790	1,5	100	50	0,642
EL010900000000	90	1	4,6	890	1,4	110	30	0,429
EL011000000000	100	1	4,9	1000	1,3	130	30	0,632
EL011020000000	102	1	4,9	1020	1,3	130	30	0,644
EL011035000000*	103,5	1	4,9	1030	1,3	130	30	0,653
EL011050000000*	105	1	5	1070	1,2	130	30	0,662
EL011100000000	110	1	5,2	1160	1,2	140	30	0,694
EL011200000000	120	1	5,2	1260	1	150	30	0,751
EL011250000000*	125	1	5,2	1310	1	150	30	0,780
EL011270000000	127	1	5,2	1330	1	150	30	0,791
EL011300000000*	130	1	5,2	1360	0,9	160	30	0,809
EL011400000000*	140	1	5,2	1460	0,9	170	30	1,155
EL011500000000	151,5	1,1	5,6	1690	0,8	180	20	0,937
EL011520000000*	152,4	1,1	5,6	1700	0,8	180	20	0,942
EL011600000000	160	1,1	6,3	1860	0,7	190	20	0,884
EL011800000000	180	1,1	6,3	2090	0,4	210	20	0,986
EL012000000000	200	1,1	6,5	2280	0,4	230	20	1,636
EL012030000000*	203,2	1,1	6,5	2310	0,4	230	20	1,660
EL012500000000	250	1,2	7,3	3390	0,4	270	10	1,355
EL013000000000	300	1,2	7,4	4140	0,3	300	10	1,612

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.
*Available on request,contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.
The technical data here reported have been measured at 23°C with 50% umidity.