




FICHA TÉCNICA · TECHNICAL DATA

1,2-2,8



+50°C

-25°C

**ARTÍCULOS DE LA MISMA SERIE
ITEMS IN THE SAME SERIES**

EOLO L (cód. EL) p.41

EOLO (cód. EO) p.42

EOLO SL (cód. ES) p.40

CÓDIGO	Ø INT.	MIN ESP.	MAX ESP.	PESO	VACIO	R. CURVATURA	LG. ROLLO	VOL.
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm/inch	mm	mm	g/m	m H ₂ O	mm	m	m ³
EE010160000000*	16	1,2	2,6	130	6	65	50	0,037
EE010190000000*	19,1	1,2	2,6	150	6	65	50	0,049
EE010200000000*	20	1,2	2,6	150	6	80	50	0,051
EE010250000000*	25	1,2	2,6	190	6	100	50	0,072
EE010300000000*	30	1,4	3	270	6	110	50	0,115
EE010320000000*	31,8	1,4	3,1	300	6	120	50	0,122
EE010350000000*	35	1,5	3,2	330	5	130	50	0,132
EE010380000000*	38,1	1,5	3,2	360	5	135	50	0,142
EE010390000000*	39	1,5	3,2	370	5	140	50	0,145
EE010400000000*	40	1,5	3,2	380	5	160	50	0,178
EE010450000000*	45	1,6	3,4	460	5	175	50	0,199
EE010500000000*	50	1,6	3,9	570	5	175	50	0,250
EE010515000000*	51,5	1,6	3,9	580	5	180	50	0,256
EE010520000000*	50,8	1,6	3,9	580	5	175	50	0,253
EE010550000000*	55	1,7	4	650	5	190	50	0,272
EE010570000000*	57	1,7	4	680	5	200	50	0,374
EE010600000000*	60	2	4,6	880	5	220	50	0,399
EE010630000000*	63,5	2	4,6	930	5	230	50	0,419
EE010650000000*	65	2	4,6	950	5	250	50	0,427
EE010700000000*	70	2	5,2	1070	5	270	50	0,463
EE010760000000*	76,2	2	5,2	1160	5	290	50	0,624
EE010800000000*	80	2	5,4	1220	5	350	30	0,523
EE010900000000*	90	2	5,4	1360	4,5	400	30	0,581
EE011000000000*	100	2,1	5,6	1520	4,5	400	30	0,641
EE011020000000*	102	2,1	5,6	1550	4,5	430	30	0,652
EE011100000000*	110	2,1	6,2	1810	4,5	470	30	0,705
EE011200000000*	120	2,1	6,3	2000	4,5	500	30	1,018
EE011270000000*	127	2,2	6,5	2220	4,5	510	30	1,075
EE011300000000*	130	2,3	6,8	2430	4	560	30	1,103
EE011400000000*	140	2,3	7	2700	4	600	20	1,183
EE011500000000*	151,5	2,5	7,3	3010	4	600	20	1,276
EE011520000000*	152,4	2,5	7,4	3080	4	650	20	1,284
EE011600000000*	160	2,7	8	3320	3,5	730	20	1,408
EE011800000000*	180	2,7	8	3720	3,5	800	20	1,568
EE012000000000*	200	2,7	8	3960	3,5	800	20	1,728
EE012030000000*	203,2	2,7	8	4020	3	1250	10	1,754
EE012500000000*	250	2,8	8,4	5260	7	1500	10	2,134

*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.