

**SCHEDA TECNICA · TECHNICAL DATA**



disponibile a magazzino  
available on stock




+50°C

-10°C


**ARTICOLI DELLA STESSA SERIE  
ITEMS IN THE SAME SERIES**



**EOLO L (cod. EL) p.41**



**EOLO SE (cod. EE) p.43**



**EOLO SL (cod. ES) p.40**

CODICE	Ø INT.	SPESS. MIN.	SPESS. MAX.	PESO	DEPR.	R. CURVATURA	LG. ROTOLO	VOL.
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm/inch	mm	mm	g/m	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
E0010130000000*	13	0,8	2,8	90	4,5	20	30	0,019
E0010160000000	16	0,8	2,8	110	4,5	20	30	0,025
E0010190000000	19,1	0,8	2,8	130	4	30	30	0,032
E0010200000000	20	0,8	2,8	140	4	30	30	0,036
E0010220000000*	22	0,8	2,8	150	4	30	30	0,036
E0010250000000	25	1	2,9	190	4	40	50	0,073
E0010300000000	30	1	3	230	3,5	50	50	0,115
E0010320000000	31,8	1	3,1	260	3,5	50	50	0,122
E0010350000000	35	1	3,3	290	3,5	50	50	0,133
E0010380000000	38,1	1	3,5	340	3	60	50	0,144
E0010390000000*	39	1	3,5	340	3	60	50	0,177
E0010400000000	40	1	3,5	350	3	60	50	0,180
E0010450000000	45	1	3,8	440	3	70	50	0,202
E0010500000000	50	1	4,1	520	3	80	50	0,251
E0010515000000*	51,5	1	4,1	540	3	80	50	0,258
E0010520000000	50,8	1	4,1	530	3	80	50	0,255
E0010550000000*	55	1	4,2	590	3	80	50	0,274
E0010600000000	60	1	4,2	640	3	90	50	0,394
E0010630000000	63,5	1	4,2	680	3	100	50	0,414
E0010650000000	65	1	4,2	690	3	100	50	0,423
E0010700000000	70	1,2	4,5	750	3	110	50	0,455
E0010760000000	76,2	1,2	4,6	840	2,5	110	50	0,615
E0010770000000*	77,7	1,2	4,6	860	2,5	120	50	0,626
E0010800000000	80	1,2	5,1	960	2,5	120	50	0,649
E0010900000000*	90	1,2	5,3	1140	2,5	140	30	0,435
E0011000000000	100	1,2	5,8	1330	2,5	150	30	0,643
E0011020000000	102	1,2	5,8	1350	2,5	150	30	0,654
E0011035000000*	103,5	1,2	5,8	1370	2,5	150	30	0,663
E0011050000000*	105	1,2	5,8	1390	2,5	160	30	0,672
E0011100000000	110	1,3	5,9	1470	2,5	160	30	0,702
E0011200000000	120	1,3	5,9	1600	2,5	180	30	0,759
E0011270000000	127	1,3	6	1720	2,5	190	30	0,801
E0011300000000*	130	1,3	6	1760	2,5	190	30	0,818
E0011400000000	140	1,3	6,1	1940	2	200	30	1,169
E0011500000000	151,5	1,3	6,4	2110	2	220	20	1,262
E0011520000000*	152,4	1,3	6,4	2130	2	220	20	1,269
E0011600000000*	160	1,5	7	2330	1,5	230	20	1,336
E0011800000000*	180	1,5	7	2620	1,5	250	20	1,490
E0012000000000	200	1,5	7,3	2900	1,5	280	20	1,648
E0012030000000*	203,2	1,5	7,3	2940	1,5	280	20	1,673
E0012500000000*	250	1,5	7,6	3800	1	330	10	1,358
E0013000000000*	300	1,5	7,8	4700	1	380	10	1,616

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

\*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% umidity.