



IT Tubo di colore blu scuro in speciale compound di PVC-P antiestrazione, con spirale di rinforzo in PVC rigido antiurto. Superficie interna completamente liscia. Resiste bene a invecchiamento, abrasione, agenti atmosferici e ozono. Su richiesta, disponibile la versione antistatica con cordingella di rame (Cod. MT 02).
• Aspirazione e mandata di olii minerali, lubrificanti, carburanti grezzi (nafta, gasolio).

EN Blue hose in special antimigration PVC compound, reinforced with an anti-shock rigid PVC spiral. Inside completely smooth. it's resistant to abrasion, ageing, weathering and ozone. On request, it is available in the AS version with copper wire (Cod. MT 02).
• Suction and delivery of mineral oils, lubricants, crude oils (naphta and diesel oil).

COD. MT
Ø mm 19-203

Spirale in PVC rigido antiurto
Anti-shock rigid PVC spiral



Tubo in PVC-P antiestrazione
antimigration PVC-P hose



SCHEDA TECNICA · TECHNICAL DATA		CODICE	Ø INT.	SPESS. MIN.	SPESS. MAX.	PESO	P.E.	P.S.	DEPR.	R. CURVATURA	LG. ROTOLO	VOLUME
		CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING R.	COIL LGTH.	VOLUME
			mm	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³
 disponibile a magazzino available on stock		MT010190000000*	19,1	4	4,3	390	8	24	10	140	50	0,071
		MT010200000000*	20	4	4,3	400	8	24	10	140	50	0,073
		MT010220000000*	22	4,1	4,4	450	8	24	10	160	50	0,079
		MT010250000000*	25	4,3	4,6	530	8	24	10	170	50	0,109
		MT010254000000*	25,4	4,3	4,6	540	8	24	10	170	50	0,111
		MT010300000000*	30	4,4	4,7	640	8	24	10	195	50	0,126
		MT010320000000*	31,8	4,4	4,7	670	8	24	10	205	50	0,132
		MT010350000000*	35	4,4	4,8	730	7	21	10	220	50	0,171
		MT010380000000*	38,1	4,4	4,8	790	7	21	10	235	50	0,206
		MT010400000000*	40	4,3	4,8	810	7	21	10	250	50	0,214
		MT010450000000*	45	4,4	4,8	910	6	18	10	275	50	0,236
		MT010500000000*	50	4,9	5,3	1130	6	18	10	300	50	0,436
		MT010520000000	50,8	4,9	5,3	1150	6	18	10	300	50	0,442
		MT010550000000*	55	5,3	5,8	1370	6	18	10	330	50	0,384
		MT010600000000*	60	5,4	5,9	1510	6	18	10	355	50	0,620
		MT010630000000*	63,5	5,6	6	1640	6	18	10	370	50	0,652
		MT010700000000*	70	5,8	6,3	1850	5	15	10	410	50	0,714
		MT010760000000	76,2	5,8	6,3	2000	5	15	10	440	50	0,767
		MT010800000000*	80	5,9	6,6	2130	5	15	10	460	30	0,671
		MT010900000000*	90	6,2	6,9	2520	4	12	10	530	30	0,747
		MT011000000000*	100	7,1	7,9	3220	4	12	9	600	30	0,889
		MT011020000000	102	7,1	7,9	3280	4	12	9	600	30	0,905
		MT011100000000*	110	7,2	8	3560	4	12	9	690	30	1,290
		MT011270000000*	127	7,3	8,1	4140	4	12	9	800	30	1,466
		MT011500000000*	151,5	9	10	6200	3	9	8,5	1300	20	1,372
		MT011520000000*	152,4	9	10	6230	3	9	8,5	1300	20	1,379
		MT012030000000*	203,2	10,7	12,5	10030	2	6	7	1200	10	1,826

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% humidity.