

# FICHA TÉCNICA · TECHNICAL DATA

2,4-7,2




+60°C

-10°C

## ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES



NETTUNO SE (cód. NX NF) p.80



NETTUNO (cód. NQ) p.107

CÓDIGO	Ø INT.	MIN ESP.	MAX ESP.	PESO	P.T.	P.R.	VACIO	R. CURVATURA	LG. ROLLO	VOLUME
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
	mm	mm	mm	g/m	bar	bar	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
NQEN0130000000*	13	2,4	2,7	150	10	30	7	75	50	0,033
NQEN0160000000*	16	2,5	2,8	190	8	24	7	90	50	0,039
NQEN0190000000*	19,1	2,6	2,9	230	7	21	7	110	50	0,054
NQEN0200000000	20	2,6	2,9	240	7	21	7	110	50	0,056
NQEN0250000000	25	2,6	2,9	290	6	18	7	130	50	0,078
NQEN0300000000	30	2,7	3	360	5	15	7	150	50	0,115
NQEN0320000000	31,8	2,7	3	380	5	15	7	155	50	0,121
NQEN0350000000	35	2,7	3,5	440	4	12	7	170	50	0,134
NQEN0380000000	38,1	2,9	3,7	510	4	12	7	180	50	0,146
NQEN0390000000*	39	2,9	3,7	530	4	12	7	190	50	0,178
NQEN0400000000	40	3	3,8	560	4	12	7	195	50	0,183
NQEN0450000000*	45	3,2	4,1	680	4	12	7	215	50	0,238
NQEN0500000000	50	3,3	4,5	810	4	12	7	235	50	0,255
NQEN0515000000*	51,5	3,3	4,5	830	4	12	7	245	50	0,261
NQEN0520000000	50,8	3,3	4,5	820	4	12	7	235	50	0,258
NQEN0550000000*	55	3,4	4,6	910	4	12	7	255	50	0,370
NQEN0570000000*	57	3,4	4,6	940	4	12	7	265	50	0,381
NQEN0600000000	60	3,4	4,6	990	4	12	7	275	50	0,399
NQEN0630000000*	63,5	3,4	4,7	1060	4	12	7	290	50	0,420
NQEN0650000000*	65	3,5	4,8	1120	4	12	7	300	50	0,430
NQEN0700000000*	70	3,7	5	1220	3	9	7	320	50	0,461
NQEN0760000000	76,2	3,9	5,2	1400	3	9	7	340	50	0,624
NQEN0777000000*	77,7	3,9	5,2	1420	3	9	7	350	50	0,634
NQEN0800000000	80	4,2	5,5	1550	3	9	7	365	50	0,786
NQEN0900000000*	90	4,4	5,9	1860	3	9	7	420	30	0,733
NQEN1000000000	100	4,8	6,4	2240	3	9	7	470	30	0,866
NQEN1020000000	102	4,8	6,4	2280	3	9	7	470	30	0,882
NQEN1035000000*	103,5	4,9	6,5	2360	3	9	7	490	30	0,895
NQEN1050000000*	105	4,9	6,5	2400	3	9	7	490	30	0,906
NQEN1100000000*	110	5	6,7	2560	3	9	6	520	30	0,948
NQEN1200000000	120	5,1	6,8	2840	3	9	6	650	30	1,368
NQEN1270000000*	127	5,2	6,9	3060	3	9	5,5	680	30	1,126
NQEN1300000000*	130	5,3	7,2	3260	3	9	5	700	30	1,155
NQEN1500000000*	151,5	6,1	8,2	4390	3	9	5	780	20	1,343
NQEN1520000000*	152,8	6,1	8,2	4420	3	9	5	780	20	1,354
NQEN2000000000*	200	6,5	10	6520	2	6	4,5	1000	10	2,130
NQEN2030000000*	203,2	6,5	10	6620	2	6	4,5	1000	10	2,161
NQEN2500000000*	250	6,8	10,5	8600	1,5	4,5	4	1800	tramo 10 m/ straight	0,734
NQEN2540000000*	254	6,8	10,5	8730	1,5	4,5	4	1800	tramo 10 m/ straight	0,756
NQEN3000000000*	300	7,2	11,1	11030	1	3	4	2000	tramo 10 m/ straight	1,038
NQEN3050000000*	304,8	7,2	11,1	11200	1	3	4	2000	tramo 10 m/ straight	1,069

\*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

\*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.