

FICHA TÉCNICA · TECHNICAL DATA



en stock
available on stock




+60°C

-10°C




CLAMP BS 4825 p.123

ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES



PLUTONE A SE (cód. PY 06) p.97



PLUTONE BIO (cód. B2) p.100

CÓDIGO	Ø INT.	Ø EST.	PESO	P.T.	P.R.	VACIO	R. CURVATURA	LG. ROLLO	VOLUMES
CODE	Ø INT.	Ø OUT.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³
PY010060012200	6	12,2	130	5	25	9,5	30	60	0,019
PY010080014200	8	14,2	155	5	25	9,5	40	60	0,024
PY010100016000	10	16	170	5	25	9,5	50	60	0,028
PY010120018000	12	18	200	5	25	9,5	50	60	0,033
PY010130019000*	13	19	210	5	25	9,5	60	60	0,038
PY010140020000	14	20	225	5	25	9,5	60	60	0,039
PY010160022400	16	22,4	270	5	25	9,5	70	60	0,048
PY010180024400	18	24,4	295	5	25	9,5	80	60	0,070
PY010190026000*	19	26	335	5	25	9,5	90	60	0,075
PY010200026000*	20	26	300	5	25	9,5	90	60	0,083
PY010200027000	20	27	350	5	25	9,5	90	60	0,086
PY010220029000	22	29	380	5	25	9,5	100	60	0,093
PY010250033000	25	33	505	4	20	9,5	110	60	0,127
PY010300038000	30	38	590	4	20	8,5	140	60	0,146
PY010320040400	32	40,4	650	4	20	8,5	140	60	0,155
PY010350043400	35	43,4	705	4	20	8,5	160	60	0,167
PY010380047000	38	47	810	4	20	8,5	170	30	0,120
PY010400049000	40	49	850	4	20	8,5	180	30	0,125
PY010450054800	45	54,8	1105	4	20	8	200	30	0,175
PY010500060000	50	60	1240	4	20	8	230	30	0,259
PY010508060800*	50,8	60,8	1260	4	20	8	230	30	0,263
PY010600071800	60	71,8	1710	3,6	18	8	270	30	0,310
PY010630074800	63	74,8	1805	3,6	18	8	280	30	0,323
PY010650076800*	65	76,8	1860	3,6	18	7,5	290	30	0,332
PY010700082000	70	82	2020	3,6	18	7	320	30	0,354
PY010760088200	76	88,2	2215	3,6	18	7	340	30	0,508
PY010800092200	80	92,2	2350	3,6	18	7	360	20	0,398
PY010900103000	90	103	3005	3	15	7	410	20	0,527
PY011020115000	102	115	3375	2,4	12	7	460	20	0,589
PY011050118000*	105	118	3470	2,4	12	7	470	20	0,604
PY011100127400	110	127,4	4800	1,6	8	9	550	20	0,652
PY011200137400	120	137,4	5205	1,2	6	9	600	20	1,055
PY011270144400	127	144,4	5540	1,2	6	9	640	20	1,109
PY011500168600	151	169,6	6910	1,2	6	9	760	20	1,303

*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.