


SCHEDA TECNICA · TECHNICAL DATA




disponibile a magazzino  
available on stock



ARTICOLI DELLA STESSA SERIE  
ITEMS IN THE SAME SERIES



SATURNO L SE (cod. XL 06) p.76



SATURNO YELLOW (cod. SY) p.106

| CODICE          | Ø INT. | SPESS. MIN.  | SPESS. MAX.  | PESO   | P.E. | P.S. | DEPR.              | R. CURVATURA | L.G. ROTOLO | VOL.           |
|-----------------|--------|--------------|--------------|--------|------|------|--------------------|--------------|-------------|----------------|
| CODE            | Ø INT. | MIN WALL TH. | MAX WALL TH. | WEIGHT | W.P. | B.P. | VACUUM             | BENDING      | COIL LGTH.  | VOL.           |
|                 | mm     | mm           | mm           | g/m    | bar  | bar  | m H <sub>2</sub> O | mm           | m           | m <sup>3</sup> |
| XL010190000000* | 19,1   | 2,2          | 2,9          | 200    | 5    | 15   | 6                  | 110          | 50          | 0,046          |
| XL010200000000  | 20     | 2,2          | 2,9          | 210    | 5    | 15   | 6                  | 110          | 50          | 0,048          |
| XL010220000000* | 22     | 2,3          | 3            | 240    | 5    | 15   | 6                  | 130          | 50          | 0,061          |
| XL010250000000  | 25     | 2,3          | 3            | 270    | 5    | 15   | 6                  | 140          | 50          | 0,078          |
| XL010255000000* | 25,5   | 2,3          | 3            | 280    | 5    | 15   | 6                  | 140          | 50          | 0,079          |
| XL010300000000  | 30     | 2,3          | 3,1          | 330    | 5    | 15   | 6                  | 170          | 50          | 0,116          |
| XL010320000000  | 31,8   | 2,4          | 3,2          | 360    | 5    | 15   | 6                  | 180          | 50          | 0,122          |
| XL010325000000* | 32,5   | 2,4          | 3,2          | 370    | 5    | 15   | 6                  | 180          | 50          | 0,124          |
| XL010350000000* | 35     | 2,5          | 3,3          | 410    | 5    | 15   | 6                  | 195          | 50          | 0,133          |
| XL010380000000  | 38,1   | 2,6          | 3,4          | 460    | 5    | 15   | 6                  | 210          | 50          | 0,172          |
| XL010390000000* | 39     | 2,6          | 3,4          | 470    | 5    | 15   | 6                  | 215          | 50          | 0,176          |
| XL010400000000  | 40     | 2,6          | 3,5          | 490    | 5    | 15   | 6                  | 220          | 50          | 0,180          |
| XL010450000000* | 45     | 2,7          | 3,6          | 570    | 5    | 15   | 6                  | 250          | 50          | 0,234          |
| XL010500000000  | 50     | 3            | 4            | 710    | 5    | 15   | 6                  | 270          | 50          | 0,251          |
| XL010520000000  | 50,8   | 3            | 4            | 720    | 5    | 15   | 6                  | 270          | 50          | 0,254          |
| XL010550000000* | 55     | 3            | 4            | 780    | 5    | 15   | 6                  | 310          | 50          | 0,363          |
| XL010570000000* | 57     | 3            | 4            | 800    | 5    | 15   | 6                  | 310          | 50          | 0,374          |
| XL010600000000  | 60     | 3            | 4,2          | 870    | 5    | 15   | 6                  | 330          | 50          | 0,394          |
| XL010630000000  | 63,5   | 3            | 4,2          | 920    | 5    | 15   | 6                  | 350          | 50          | 0,414          |
| XL010650000000* | 65     | 3,1          | 4,3          | 970    | 5    | 15   | 6                  | 360          | 50          | 0,636          |
| XL010700000000* | 70     | 3,2          | 4,5          | 1050   | 4    | 12   | 6                  | 450          | 50          | 0,683          |
| XL010750000000* | 75     | 3,3          | 4,6          | 1160   | 4    | 12   | 6                  | 500          | 50          | 0,727          |
| XL010760000000  | 76,2   | 3,3          | 4,6          | 1180   | 4    | 12   | 6                  | 500          | 50          | 0,738          |
| XL010800000000  | 80     | 3,6          | 5            | 1350   | 4    | 12   | 6                  | 550          | 50          | 0,778          |
| XL010900000000* | 90     | 4,2          | 6            | 1870   | 3    | 9    | 6                  | 630          | 30          | 0,588          |
| XL011000000000  | 100    | 4,6          | 6,4          | 2210   | 3    | 9    | 6                  | 710          | 30          | 0,866          |
| XL011020000000  | 102    | 4,6          | 6,4          | 2250   | 3    | 9    | 6                  | 710          | 30          | 0,882          |
| XL011100000000* | 110    | 5            | 6,7          | 2560   | 3    | 9    | 6                  | 720          | 30          | 1,264          |
| XL011200000000* | 120    | 5            | 6,8          | 2810   | 3    | 9    | 6                  | 730          | 30          | 1,368          |
| XL011270000000* | 127    | 5,1          | 6,9          | 3030   | 3    | 9    | 6                  | 740          | 30          | 1,442          |
| XL011500000000* | 151,5  | 5,9          | 7,8          | 4160   | 3    | 9    | 6                  | 800          | 20          | 1,337          |
| XL011520000000* | 152,4  | 5,9          | 7,8          | 4180   | 3    | 9    | 6                  | 800          | 20          | 1,344          |
| XL012000000000* | 200    | 6,5          | 10           | 6510   | 2    | 6    | 4,5                | 1000         | 10          | 1,760          |

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.  
\*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.  
The technical data here reported have been measured at 23°C with 50% humidity.