

# SATURNO YELLOW



**ES** Tubo de PVC-P de color amarillo transparente con espiral de refuerzo de PVC rígido antichoques de color marfil. Superficie interna completamente lisa y superficie externa semilisa. Ligero y maneable. Muy resistente al aplastamiento, a los agentes atmosféricos y a numerosas substancias químicas. Calidad alimentaria, según UE 10/2011 (clases A, B, C).

• Para riego; en agricultura, se utiliza para la aspiración y el transporte de líquidos, fertilizantes y soluciones de uso común en el sector; aspiración y transporte de líquidos alimentarios. Se utiliza en camiones cisterna y en el sector náutico como manguera de transporte de líquidos en bombas de sentina.

**EN** Transparent yellow PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, weathering and to most chemicals. Suitable for suction and delivery of food liquids, according to EU 10/2011 (classes A, B, C).

• Excellent in agriculture, for irrigation and suction of liquids, fertilizers and solutions used in agriculture. It is used on tank trucks; in the marine industry, as liquid transfer hose on bilge pumps.



**CÓD. SY**  
Ø mm 19-200

Tubo en PVC-P  
PVC-P hose



Espiral de PVC rígido antichoques  
Anti-shock rigid PVC spiral



FICHA TÉCNICA · TECHNICAL DATA		CÓDIGO	Ø INT.	MIN ESP.	MAX ESP.	PESO	P.T.	P.R.	VACIO	R. CURVATURA	LG. ROLLO	VOLUME
		CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
			mm	mm	mm	g/m	bar	bar	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
+60°C	-10°C	SY010190000000*	19,1	2,2	2,9	200	5	15	6	110	50	0,046
		SY010200000000*	20	2,2	2,9	210	5	15	6	110	50	0,048
2,2-6,5		SY010220000000*	22	2,3	3	240	5	15	6	130	50	0,061
		SY010250000000*	25	2,3	3	270	5	15	6	140	50	0,078
ARTÍCULOS DE LA MISMA SERIE ITEMS IN THE SAME SERIES		SY010255000000*	25,5	2,3	3	280	5	15	6	140	50	0,079
		SY010300000000*	30	2,3	3,1	330	5	15	6	170	50	0,116
SATURNO L (cód. XL 01) p.75		SY010320000000*	31,8	2,4	3,2	360	5	15	6	180	50	0,122
		SY010325000000*	32,5	2,4	3,2	370	5	15	6	180	50	0,124
SATURNO L SE (cód. XL 06) p.76		SY010350000000*	35	2,5	3,3	410	5	15	6	195	50	0,133
		SY010380000000*	38,1	2,6	3,4	460	5	15	6	210	50	0,172
		SY010390000000*	39	2,6	3,4	470	5	15	6	215	50	0,176
		SY010400000000*	40	2,6	3,5	490	5	15	6	220	50	0,180
		SY010450000000*	45	2,7	3,6	570	5	15	6	250	50	0,234
		SY010500000000*	50	3	4	710	5	15	6	270	50	0,251
		SY010520000000*	50,8	3	4	720	5	15	6	270	50	0,254
		SY010550000000*	55	3	4	780	5	15	6	310	50	0,363
		SY010570000000*	57	3	4	800	5	15	6	310	50	0,374
		SY010600000000*	60	3	4,2	870	5	15	6	330	50	0,394
		SY010630000000*	63,5	3	4,2	920	5	15	6	350	50	0,414
		SY010650000000*	65	3,1	4,3	970	5	15	6	360	50	0,636
		SY010700000000*	70	3,2	4,5	1050	4	12	6	450	50	0,683
		SY010750000000*	75	3,3	4,6	1160	4	12	6	500	50	0,727
		SY010760000000*	76,2	3,3	4,6	1180	4	12	6	500	50	0,738
		SY010800000000*	80	3,6	5	1350	4	12	6	550	50	0,778
		SY010900000000*	90	4,2	6	1870	3	9	6	630	30	0,588
		SY011000000000*	100	4,6	6,4	2210	3	9	6	710	30	0,866
		SY011020000000*	102	4,6	6,4	2250	3	9	6	710	30	0,882
		SY011100000000*	110	5	6,7	2560	3	9	6	720	30	1,264
		SY011200000000*	120	5	6,8	2810	3	9	6	730	30	1,368
		SY011270000000*	127	5,1	6,9	3030	3	9	6	740	30	1,442
		SY011500000000*	151,5	5,9	7,8	4160	3	9	6	800	20	1,337
		SY011520000000*	152,4	5,9	7,8	4180	3	9	6	800	20	1,344
		SY012000000000*	200	6,5	10	6510	2	6	4,5	1000	10	1,76

\*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

\*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% humidity.