


FICHA TÉCNICA · TECHNICAL DATA


 2,2-6,5


+60°C

-10°C

**ARTÍCULOS DE LA MISMA SERIE
ITEMS IN THE SAME SERIES**


SATURNO L (cód. XL 01) p.75



SATURNO L SE (cód. XL 06) p.76

CÓDIGO	Ø INT.	MIN ESP.	MAX ESP.	PESO	P.T.	P.R.	VACIO	R. CURVATURA	LG. ROLLO	VOLUME
CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
	mm	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³
SY010190000000*	19,1	2,2	2,9	200	5	15	6	110	50	0,046
SY010200000000*	20	2,2	2,9	210	5	15	6	110	50	0,048
SY010220000000*	22	2,3	3	240	5	15	6	130	50	0,061
SY010250000000*	25	2,3	3	270	5	15	6	140	50	0,078
SY010255000000*	25,5	2,3	3	280	5	15	6	140	50	0,079
SY010300000000*	30	2,3	3,1	330	5	15	6	170	50	0,116
SY010320000000*	31,8	2,4	3,2	360	5	15	6	180	50	0,122
SY010325000000*	32,5	2,4	3,2	370	5	15	6	180	50	0,124
SY010350000000*	35	2,5	3,3	410	5	15	6	195	50	0,133
SY010380000000*	38,1	2,6	3,4	460	5	15	6	210	50	0,172
SY010390000000*	39	2,6	3,4	470	5	15	6	215	50	0,176
SY010400000000*	40	2,6	3,5	490	5	15	6	220	50	0,180
SY010450000000*	45	2,7	3,6	570	5	15	6	250	50	0,234
SY010500000000*	50	3	4	710	5	15	6	270	50	0,251
SY010520000000*	50,8	3	4	720	5	15	6	270	50	0,254
SY010550000000*	55	3	4	780	5	15	6	310	50	0,363
SY010570000000*	57	3	4	800	5	15	6	310	50	0,374
SY010600000000*	60	3	4,2	870	5	15	6	330	50	0,394
SY010630000000*	63,5	3	4,2	920	5	15	6	350	50	0,414
SY010650000000*	65	3,1	4,3	970	5	15	6	360	50	0,636
SY010700000000*	70	3,2	4,5	1050	4	12	6	450	50	0,683
SY010750000000*	75	3,3	4,6	1160	4	12	6	500	50	0,727
SY010760000000*	76,2	3,3	4,6	1180	4	12	6	500	50	0,738
SY010800000000*	80	3,6	5	1350	4	12	6	550	50	0,778
SY010900000000*	90	4,2	6	1870	3	9	6	630	30	0,588
SY011000000000*	100	4,6	6,4	2210	3	9	6	710	30	0,866
SY011020000000*	102	4,6	6,4	2250	3	9	6	710	30	0,882
SY011100000000*	110	5	6,7	2560	3	9	6	720	30	1,264
SY011200000000*	120	5	6,8	2810	3	9	6	730	30	1,368
SY011270000000*	127	5,1	6,9	3030	3	9	6	740	30	1,442
SY011500000000*	151,5	5,9	7,8	4160	3	9	6	800	20	1,337
SY011520000000*	152,4	5,9	7,8	4180	3	9	6	800	20	1,344
SY012000000000*	200	6,5	10	6510	2	6	4,5	1000	10	1,76

*Disponible bajo pedido, para cantidades a convenir con el departamento de ventas.

*Available on request, contact our sales office for more info and quantities.

Los datos técnicos indicados se midieron a 23°C y 50% de humedad.

The technical data here reported have been measured at 23°C with 50% umidity.