

FICHA TÉCNICA · TECHNICAL DATA



+90°C picos
peaks
+125°C

-40°C



F2 W2 p.122

Abrazaderas doble puente W2/ Double bridge W2

**ARTÍCULOS DE LA MISMA SERIE
ITEMS IN THE SAME SERIES**


VULCANO STONE (cod. TH 01) p.21

CODIGO	Ø INT.	MIN ESP.	PESO	VACIO	R. CURVATURA	LG. ROLLO	VOL.
CODE	Ø INT.	MIN WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm/inch	mm	g/m	m H ₂ O	mm	m	m ³
TH070400000000*	40	2,5	945	9,7	180	15	0,10
TH070450000000*	45	2,5	1210	9,7	200	15	0,11
TH070510000000*	51	2,5	1350	9,7	200	15	0,12
TH070600000000*	60	2,5	1560	9,7	250	15	0,19
TH070800000000*	80	2,5	2025	9,7	300	tramo 10 m/ straight	0,38
TH070900000000*	90	2,5	2255	9,7	350	tramo 10 m/ straight	0,42
TH071000000000*	100	2,5	2660	9,5	500	tramo 10 m/ straight	0,46
TH071020000000*	102	2,5	2710	9,5	500	tramo 10 m/ straight	0,47
TH071270000000*	127	2,5	3710	9	600	tramo 10 m/ straight	0,20
TH071520000000*	152	2,5	4235	8	800	tramo 6 m/ straight	0,17
TH071750000000*	175	2,5	5370	6	900	tramo 6 m/ straight	0,22
TH072000000000*	200	2,5	6110	4	1000	tramo 6 m/ straight	0,28
TH072030000000*	203	2,5	6195	4	1000	tramo 6 m/ straight	0,28
TH072250000000*	225	2,5	6855	4	1200	tramo 6 m/ straight	0,35
TH072500000000*	250	2,5	7595	4	1400	tramo 6 m/ straight	0,42
TH072540000000*	254	2,5	7710	4	1400	tramo 6 m/ straight	0,44

Los datos técnicos indicados se midieron a 23°C y 50% de humedad. *The technical data here reported have been measured at 23°C with 50% umidity.*
*Disponibile bajo pedido, para cantidades a convenir con el departamento de ventas. **Available on request, contact our sales office for more info and quantities.*