

# SCHEDA TECNICA · TECHNICAL DATA



CLAMP BS 4825 p.123

| CODICE          | Ø INT.       | Ø EST. | PESO   | P.E. | P.S. | DEPR.              | R. CURVATURA | LG. ROTOLO | VOLUME         |
|-----------------|--------------|--------|--------|------|------|--------------------|--------------|------------|----------------|
| CODE            | Ø INT.       | Ø OUT. | WEIGHT | W.P. | B.P. | VACUUM             | BENDING      | COIL LGTH. | VOLUME         |
|                 | mm           | mm     | g/m    | bar  | bar  | m H <sub>2</sub> O | mm           | m          | m <sup>3</sup> |
| WK010127025100* | 12,7/ 1/2"   | 25,1   | 530    | 10   | 40   | 10                 | 45           | 4          | 0,003          |
| WK010190031400* | 19,05/ 3/4"  | 31,4   | 700    | 10   | 40   | 10                 | 65           | 4          | 0,004          |
| WK010254037800* | 25,4/ 1"     | 37,8   | 970    | 10   | 40   | 10                 | 80           | 4          | 0,006          |
| WK010318044200* | 31,8/ 1 1/4" | 44,2   | 1050   | 10   | 40   | 10                 | 120          | 4          | 0,008          |
| WK010381050500* | 38,1/ 1 1/2" | 50,5   | 1410   | 10   | 40   | 10                 | 150          | 4          | 0,010          |
| WK010508063200* | 50,8/ 2"     | 63,2   | 1660   | 10   | 40   | 10                 | 180          | 4          | 0,016          |
| WK010635075900* | 63,5/ 2 1/2" | 75,9   | 2000   | 7    | 28   | 10                 | 220          | 4          | 0,023          |
| WK010762088600* | 76,2/ 3"     | 88,6   | 2430   | 4    | 16   | 10                 | 250          | 4          | 0,032          |

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

\*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% umidity.