

FICHA TÉCNICA - TECHNICAL DATA

 en stock
available on stock

**ARTÍCULOS DE LA MISMA SERIE
ITEMS IN THE SAME SERIES**

APOLLO SUPERFLEX (cód. AS) p.70

CÓDIGO CODE	Ø INT. Ø INT.	MIN ESP. MIN WALL TH.	MAX ESP. MAX WALL TH.	PESO WEIGHT	P.T. W.P.	P.R. B.P.	VACÍO VACUUM	R. CURVATURA BENDING	LG. ROLLO COIL LGTH.	VOLUMEN VOLUME
	mm	mm	mm	g/m	bar	bar	m H ₂ O	m ²	m	m ³
SF010520000000	50,8	4,4	4,9	970	3,3	10	9	160	50	0,262
SF010550000000*	55	4,6	5,1	1100	3,3	10	9	160	50	0,282
SF010600000000*	60	4,8	5,3	1260	3	9	9	200	50	0,407
SF010630000000	63,5	4,9	5,5	1380	3	9	9	210	50	0,429
SF010650000000*	65	5	5,6	1440	3	9	9	210	50	0,439
SF010700000000*	70	5,1	5,7	1530	3	9	9	225	50	0,469
SF010760000000	76,2	5,1	6,1	1710	3	9	9	250	50	0,636
SF010800000000	80	5,1	7,0	1960	2,5	7,5	9	270	50	0,677
SF010900000000	90	5,2	7,2	2260	2,5	7,5	9	300	30	0,601
SF011020000000	102	5,9	7,8	2810	2,2	6,5	9	335	30	0,677
SF011050000000	105	6	7,8	2910	2,2	6,5	9	335	30	0,695
SF011100000000	110	6,1	7,8	3030	2	6	8	360	30	0,723
SF011270000000	127	6,3	7,9	3560	1,8	5,5	8	410	30	1,097
SF011520000000	152,4	7,4	9,1	5020	1,5	4,5	8	500	20	1,310

 *Disponible bajo pedido, para cantidades a
convenir con el departamento de ventas.

 *Available on request, contact our sales office
for more info and quantities.

 Los datos técnicos indicados se midieron a 23°C y
50% de humedad.

 The technical data here reported have been
measured at 23°C with 50% humidity.