

**FICHA TÉCNICA · TECHNICAL DATA**


**+90°C**

 picos  
peaks  
+125°C

**-40°C**

**F2 W2 p.122**

Abrazaderas doble puente W2 / Double bridge W2

**ARTÍCULOS DE LA MISMA SERIE  
ITEMS IN THE SAME SERIES**

**VULCANO STONE PLUS (cód.TH 07) p.22**

CÓDIGO CODE	Ø INT. Ø INT.	MIN ESP. MIN WALL TH.	PESO WEIGHT	VACÍO VACUUM	R. CURVATURA BENDING	LG. ROLLO COIL LGTH.	VOL. VOL.
	mm/inch	mm	g/m	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
TH010380000000*	38	2	800	9,7	150	15	0,06
TH010400000000*	40	2	840	9,7	160	15	0,07
TH010450000000*	45	2	930	9,7	180	15	0,11
TH010510000000*	51	2	1140	9,7	204	15	0,12
TH010600000000*	60	2	1320	9,7	240	15	0,18
TH010630000000*	63	2	1380	9,7	250	15	0,19
TH010650000000*	65	2	1420	9,7	250	15	0,20
TH010700000000*	70	2	1520	9,5	280	15	0,21
TH010760000000*	76	2	1640	9,5	305	15	0,25
TH010800000000*	80	2	1720	9,5	320	15	0,26
TH010900000000*	90	2	1925	9,5	360	15	0,29
TH011000000000*	100	2	2275	9,5	400	10	0,32
TH011020000000*	102	2	2320	9,5	410	10	0,33
TH011060000000*	110	2	2490	9,4	440	10	0,35
TH011150000000*	115	2	2600	9,4	460	10	0,37
TH011200000000*	120	2	2705	9,2	480	10	0,68
TH011270000000*	127	2	2965	9	510	tramo 10 m/ straight	0,72
TH011300000000*	130	2	3030	9	520	tramo 10 m/ straight	0,73
TH011400000000*	140	2	3255	8,7	560	tramo 10 m/ straight	0,23
TH011500000000*	150	2	3475	8,5	600	tramo 10 m/ straight	0,27
TH011520000000*	152	2	3520	8,2	610	tramo 10 m/ straight	0,27
TH011600000000*	160	2	4245	8	640	tramo 10 m/ straight	0,30
TH011800000000*	180	2	4750	7	810	tramo 10 m/ straight	0,37
TH012000000000*	200	2	5260	6	1000	tramo 10 m/ straight	1,64
TH012030000000*	203	2	5335	6	1015	tramo 10 m/ straight	0,47
TH012200000000*	220	2	5770	5	-	tramo 6 m/ straight	0,327
TH012280000000*	228	2	5975	5	-	tramo 6 m/ straight	0,35
TH012400000000*	240	2	6280	4	-	tramo 6 m/ straight	0,39
TH012450000000*	245	2	6405	4	-	tramo 6 m/ straight	0,40
TH012500000000*	250	2	6535	4	-	tramo 6 m/ straight	0,42
TH012540000000*	254	2	6635	4	-	tramo 6 m/ straight	0,43

 \*Disponible bajo pedido, para cantidades a  
convenir con el departamento de ventas.

 \*Available on request contact our sales office  
for more info and quantities.

 Los datos técnicos indicados se midieron a 23°C y  
50% de humedad.

 The technical data here reported have been  
measured at 23°C with 50% humidity.