

SPIRALPRESS MILK



IT

Tubo bianco in speciale PVC-P appositamente studiato per il settore lattiero-caseario, con spirale in PVC rigido antiurto color azzurro e rinforzo tessile ad alta tenacità. Parete e spirale di grado alimentare.

Grazie al rinforzo tessile presenta una buona resistenza a pressioni elevate, **senza deformazioni longitudinali o trasversali**; la spirale sporgente facilita le operazioni di scorrimento sul suolo. Idoneo al contatto alimenti secondo UE 10/2011 (classi A,B,C, D1). Spirulina disponibile su richiesta su tutta la gamma diametri (cod. SC EN).

• Trasporto in aspirazione e mandata di latte e derivati, ideale su camion cisterna per la raccolta latte.

EN

White special PVC-P hose, reinforced with a light blue anti-shock rigid PVC spiral and polyester yarn. Food grade wall and hard plastic spiral. Specially conceived for the dairy industry, to withstand high pressure applications,

without elongation, thanks to the textile reinforcement. The exposed PVC corrugated helix allows less resistance to dragging. Food grade hose wall and spiral. Food grade, according to EU 10/2011 (classes A, B, C, D1). Banding coil available on request, throughout the diameter range (Code SC EN).

• Suction and discharge of milk and by-products, ideal on milk tanker trucks.

COD. SK

Ø mm 38-102

Spirale in PVC rigido antiurto
Anti-shock rigid PVC spiral



Tubo in speciale PVC-P
Special PVC-P hose


Rinforzo tessile in fibra di poliestere
Polyester yarn reinforcement



SCHEDA TECNICA - TECHNICAL DATA




+80°C
-10°C




SC WT p.125
Spiralina rossa/ Red banding coil

ARTICOLI DELLA STESSA SERIE ITEMS IN THE SAME SERIES



SPIRALPRESS WT (cod. WT) p.72



SPIRALPRESS ENO (cod. BS EN) p.111

CODICE CODE	Ø INT. Ø INT.	SPES. MIN. MIN WALL TH.	SPES. MAX. MAX WALL TH.	PESO WEIGHT	P.E. W.P.	DEPR. VACUUM	R. CURVATURA BENDING	LG. ROTOLO COIL LGTH.	VOLUME VOLUME	LG. SPIRALINA BANDING COIL LGTH.
	mm	mm	mm	g/m	bar 23°C/ 80°C	m H ₂ O	mm	m	m ³	mm
SK010380000000*	38,1/ 1 1/2"	3	7,1	820	8/2,5	9,5	90	30	0,134	153
SK010400000000*	40	3	7,1	840	8/2,5	9,5	100	30	0,139	152
SK010500000000*	50	3	7,7	1125	7/2,5	9,5	160	30	0,251	180
SK010508000000*	50,8/ 2"	3	7,7	1140	7/2,5	9,5	160	30	0,254	180
SK010600000000*	60	3	8,4	1280	7/2,5	9,5	180	30	0,332	203
SK010635000000*	63,5/ 2 1/2"	3	8,4	1350	6/2	9,5	210	30	0,347	203
SK010760000000*	76,3/ 3"	3,5	9,8	1975	6/2	9	200	30	0,414	225
SK010800000000*	80	3,5	10,4	2255	6/2	9	210	30	0,581	225
SK011000000000*	100	3,5	10,4	2675	6/2	9	300	30	0,928	240
SK011020000000*	101,6/ 4"	3,5	10,5	2750	6/2	9	300	30	0,942	240

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% humidity.