

IT Tubo in PVC/NBR di colore nero rinforzato con spirale in PVC rigido antiurto di colore grigio. Grazie alla sua particolare formulazione mista a gomma nitrilica, mantiene un'elevata flessibilità a temperature estreme. Il suo profilo con spirale leggermente sporgente, garantisce un facile scorrimento sul terreno e una raccordatura semplice e sicura. Versione AS con cordicella di rame disponibile su richiesta (Cod. SF 02).

• Aspirazione e mandata di liquidi industriali e acque reflue, è particolarmente adatto per l'impiego su veicoli per il trattamento acque e carri botte, anche a bassissime temperature.

EN Black coloured PVC/NBR hose, reinforced with a grey anti-shock rigid PVC spiral. Its particular mixed rubber nitrilic formulation enhances to keep high flexibility at extreme low temperatures. Its profile with a slightly protruding spiral guarantees an easy dragging on the ground and an easy and safe connection. AS version with copper wire available on request (Cod. SF 02).

• Suction and discharge of liquids and wastewater in general; ideal to be used on tank trucks, even at extremely low temperatures.



APOLLO SUPERFLEX 2

COD. SF 01 · Ø mm 50,8-152,4



Spirale in PVC rigido antiurto leggermente esposta
Slightly exposed anti-shock rigid PVC spiral



Tubo in PVC-NBR
PVC-NBR hose

ARTICOLI DELLA STESSA SERIE · ITEMS IN THE SAME SERIES



APOLLO SUPERFLEX



APOLLO TOTAL

SCHEDA TECNICA · TECHNICAL DATA

JP = Just pick, in stock

APOLLO SUPERFLEX 2	Ø int.		Spess min Min wall thick	Spess max max wall thick	Peso Weight	P.E. W.P.	P.S. B.P.	Depr. Vacuum	R. curvatura Bending r.	Lg. Rotolo Coil lgth.	Volume	Disponibilità Availability
	mm	inches										
CODICE/CODE	mm	inches	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³	
SF010520000000	50,8	2	4,4	4,9	970	3,3	10	9	160	50	0,349	in stock
SF010550000000*	55		4,6	5,1	1100	3,3	10	9	160	50	0,376	su richiesta/on request*
SF010600000000*	60		4,8	5,3	1260	3	9	9	200	50	0,407	su richiesta/on request*
SF010630000000	63,5	2 1/2	4,9	5,5	1380	3	9	9	210	50	0,429	✓
SF010650000000*	65		5	5,6	1440	3	9	9	210	50	0,439	su richiesta/on request*
SF010700000000*	70		5,1	5,7	1530	3	9	9	225	50	0,586	su richiesta/on request*
SF010760000000	76,2	3	5,1	6,1	1710	3	9	9	250	50	0,636	in stock
SF010800000000	80		5,1	7	1960	2,5	7,5	9	270	50	0,677	in stock
SF010900000000	90		5,2	7,2	2260	2,5	7,5	9	300	30	0,601	✓
SF011020000000	102		5,9	7,8	2810	2,2	6,5	9	335	30	0,677	in stock
SF011050000000*	105		6	7,8	2910	2,2	6,5	9	335	30	0,695	su richiesta/on request*
SF011100000000	110		6,1	7,8	3030	2	6	8	360	30	0,723	in stock
SF011200000000	120		6,3	7,9	3370	1,8	5,5	8	360	30	1,391	✓
SF011250000000*	125		6,3	7,9	3510	1,8	5,5	8	410	30	1,081	su richiesta/on request*
SF011270000000*	127	5	6,3	7,9	3560	1,8	5,5	8	410	30	1,097	su richiesta/on request*
SF011520000000*	152,4	6	7,4	9,1	5020	1,5	4,5	8	500	20	1,310	su richiesta/on request*

* Diametri su richiesta per quantitativi minimi (MOQ), salvo disponibilità a magazzino · * Diameters available on request for minimum order quantities (MOQ), unless in stock



I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità
The technical data here reported have been measured at 23°C with 50% humidity