

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità  
 The technical data here reported have been measured at 23°C with 50% humidity

## SCHEDA TECNICA · TECHNICAL DATA

NEXT 15	ø int.		Spess min min wall thick	Peso Weight	Depr. Vacuum	R. curvatura Bending r.	Lg. Rotolo Coil lgth.	Volume	Disponibilità Availability	Fascetta W2 Double bridge W2
	mm	inches								
<b>CODICE/CODE</b>	mm	inches	mm	g/m	m H <sub>2</sub> o	mm	m	m <sup>3</sup>		
<b>N5010400000000</b>	40		1,5	490	9,5	90	30	0,122	✓	-
<b>N5010450000000</b>	45		1,5	630	9	90	30	0,137	✓	-
<b>N5010520000000</b>	50,8	2	1,5	675	9	90	30	0,189	✓	-
<b>N5010600000000</b>	60		1,5	775	8,5	95	30	0,219	✓	-
<b>N5010630000000</b>	63,5	2 1/2	1,5	895	8	100	30	0,312	✓	-
<b>N5010650000000</b>	65		1,5	915	7,5	100	30	0,319	✓	-
<b>N5010760000000</b>	76,2	3	1,5	1100	7	110	30	0,370	✓	-
<b>N5010800000000</b>	80		1,5	1150	6	110	30	0,386	✓	-
<b>N5010900000000</b>	90		1,5	1285	5	115	20	0,286	✓	-
<b>N5011000000000</b>	100		1,5	1420	4	120	20	0,315	✓	F2 W2 100.0 127.0
<b>N5011020000000</b>	102		1,5	1445	4	120	20	0,321	✓	
<b>N5011100000000</b>	110		1,5	1405	3,2	130	20	0,516	✓	
<b>N5011200000000</b>	120		1,5	1530	3	150	20	0,559	✓	
<b>N5011270000000</b>	127	5	1,5	1615	2,9	150	20	0,589	✓	
<b>N5011400000000</b>	140		1,5	2080	2,4	170	20	0,650	✓	F2 W2 130.0 190.0
<b>N5011520000000</b>	152,4	6	1,5	2260	2	200	20	0,834	✓	
<b>N5011600000000</b>	160		1,5	2370	1,8	250	20	0,872	✓	
<b>N5011800000000</b>	180		1,5	2655	1,5	300	20	0,975	✓	F2 W2 200.0 230.0
<b>N5012030000000</b>	203,2	8	1,5	3310	1,2	300	15	1,099	✓	

\* Diametri su richiesta per quantitativi minimi (MOQ), salvo disponibilità a magazzino · \* Diameters available on request for minimum order quantities (MOQ), unless in stock