

NETTUNO

COD. NQ 01 · Ø mm 13-305


IT Tubo trasparente in PVC-P, con spirale di rinforzo in PVC-P rigido antiurto color avorio. Completamente liscio internamente, leggero e molto flessibile. Resistente a carichi, agli agenti atmosferici e a molti prodotti chimici. Versione antistatica con cordicella di rame disponibile su richiesta (Cod.NQ 02). Alimentare secondo UE 10/2011 (classi A,B, C, D1); indicato per il passaggio di latte e derivati nel settore lattiero caseario.

• Soluzione ideale per il trasporto in aspirazione e mandata di polveri alimentari, granaglie, alimenti liofilizzati, bevande, succhi di frutta, aceto, vino e liquori con concentrazione alcolica fino a 50%. In agricoltura, impiegato su camion cisterna e veicoli spandiconcime liquido.

EN Transparent PVC-P hose, reinforced with an ivory anti-shock rigid PVC spiral. Smooth inside, light and very flexible. Resistant to loads, weathering and to a wide range of chemicals. The AS version with copper wire is available on request (Cod. NQ 02). Food grade, according to EU 10/2011 (classes A, B, C, D1) and suitable for passage of milk and dairy products.

• Ideal solution for suction and delivery of food powders flours, light grains, freeze dried foodstuffs as well as for liquid in general, beverage, juices, milk and by-products, vinegar, wines and liquors with an alcohol content up to 50%. In agriculture, used on tank trucks and manure spreaders.

ARTICOLI DELLA STESSA SERIE · ITEMS IN THE SAME SERIES



NETTUNO SE



BACCO



NETTUNO ENO

SCHEDA TECNICA · TECHNICAL DATA

NETTUNO	Ø int.		Spess min Min wall thick	Spess max max wall thick	Peso Weight	P.E. W.P.	P.S. B.P.	Depr. Vacuum	R. curvatura Bending r.	Lg. Rotolo Coil lgth.	Volume	Disponibilità Availability
	mm	inches										
CODICE/CODE	mm	inches	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³	
NQ010130000000	13		2,4	3,1	160	10	30	7	75	50	0,035	✓
NQ010160000000	16		2,5	3,2	200	8	24	7	90	50	0,040	✓
NQ010190000000*	19,1		2,6	3,3	240	7	21	7	110	50	0,056	su richiesta/on request*
NQ010200000000	20		2,6	3,3	250	7	21	7	110	50	0,057	in stock
NQ010220000000*	22		2,6	3,3	270	7	20	7	110	50	0,062	su richiesta/on request*
NQ010250000000	25		2,6	3,3	300	6	18	7	130	50	0,080	in stock
NQ010300000000	30		2,7	3,4	370	5	15	7	150	50	0,118	in stock
NQ010320000000	31,8		2,7	3,4	390	5	15	7	155	50	0,124	in stock
NQ010350000000	35		2,7	3,8	460	4	12	7	170	50	0,136	✓
NQ010380000000	38,1	1 1/2	2,9	4	530	4	12	7	180	50	0,148	in stock
NQ010390000000*	39		2,9	4	540	4	12	7	190	50	0,180	su richiesta/on request*
NQ010400000000	40		3	4,1	580	4	12	7	195	50	0,185	in stock
NQ010450000000	45		3,2	4,4	700	4	12	7	215	50	0,241	✓
NQ010500000000	50		3,3	4,8	840	4	12	7	235	50	0,343	in stock
NQ010515000000*	51,5		3,3	4,8	860	4	12	7	245	50	0,352	su richiesta/on request*
NQ010520000000	50,8	2	3,3	4,8	850	4	12	7	235	50	0,348	✓
NQ010550000000*	55		3,4	4,9	940	4	12	7	255	50	0,373	su richiesta/on request*
NQ010570000000*	57		3,4	4,9	970	4	12	7	265	50	0,385	su richiesta/on request*
NQ010600000000	60		3,4	4,9	1020	4	12	7	275	50	0,402	in stock
NQ010630000000	63,5	2 1/2	3,4	5	1100	4	12	7	290	50	0,423	in stock
NQ010650000000*	65		3,5	5,1	1160	4	12	7	300	50	0,433	su richiesta/on request*
NQ010700000000	70		3,7	5,3	1260	3	9	7	320	50	0,580	in stock
NQ010750000000	75		3,9	5,5	1420	3	9	7	340	50	0,619	✓
NQ010760000000	76,2	3	3,9	5,5	1440	3	9	7	340	50	0,628	in stock
NQ010770000000*	77,7		3,9	5,5	1470	3	9	7	350	50	0,639	su richiesta/on request*
NQ010800000000	80		4,2	5,8	1590	3	9	7	365	50	0,660	in stock
NQ010900000000	90		4,4	6,2	1920	3	9	7	420	30	0,737	✓
NQ011000000000	100		4,8	6,7	2290	3	9	7	470	30	0,871	in stock
NQ011020000000	102		4,8	6,7	2340	3	9	7	470	30	0,886	✓
NQ011035000000*	103,5		4,9	6,8	2420	3	9	7	490	30	0,899	su richiesta/on request*
NQ011050000000*	105		4,9	6,8	2450	3	9	7	490	30	0,911	su richiesta/on request*
NQ011100000000*	110		5	7	2620	3	9	6	520	30	0,952	su richiesta/on request*
NQ011200000000*	120		5,1	7,1	2910	3	9	6	650	30	1,031	su richiesta/on request*
NQ011270000000*	127	5	5,2	7,2	3130	3	9	5,5	680	30	1,131	su richiesta/on request*
NQ011300000000*	130		5,3	7,5	3340	3	9	5	700	30	1,160	su richiesta/on request*
NQ011400000000*	140		5,7	8	3900	3	9	5	750	20	1,248	su richiesta/on request*
NQ011500000000*	151,5		6,1	8,5	4480	3	9	5	780	20	1,348	su richiesta/on request*
NQ011520000000*	152,8		6,1	8,5	4510	3	9	5	780	20	1,358	su richiesta/on request*
NQ011600000000*	160		6,3	9,1	4860	2	6	4,5	850	20	1,426	su richiesta/on request*
NQ012000000000*	200		6,5	10,3	6640	2	6	4,5	1000	10	2,135	su richiesta/on request*
NQ012030000000*	203,2	8	6,5	10,3	6740	2	6	4,5	1000	10	2,166	su richiesta/on request*
NQ012500000000*	250		6,8	10,8	8750	1,5	4,5	4	1800	10 m pz. dritti/straight	0,738	su richiesta/on request*
NQ012540000000*	254	10	6,8	10,8	8890	1,5	4,5	4	1800	10 m pz. dritti/straight	0,760	su richiesta/on request*
NQ013000000000*	300		7,2	11,4	11220	1	3	4	2000	10 m pz. dritti/straight	1,042	su richiesta/on request*
NQ013050000000*	304,8	12	7,2	11,4	11400	1	3	4	2000	10 m pz. dritti/straight	1,073	su richiesta/on request*

* Diametri su richiesta per quantitativi minimi (MOQ), salvo disponibilità a magazzino · * Diameters available on request for minimum order quantities (MOQ), unless in stock

JP versione AS/AS version	Ø int.		Spess min Min wall thick	Spess max max wall thick	Peso Weight	P.E. W.P.	P.S. B.P.	Depr. Vacuum	R. curvatura Bending r.	Lg. Rotolo Coil lgth.	Volume	Disponibilità Availability
	mm	inches										
NQ020500000000	50		3,3	4,50	870	4	12	7	235	50	0,255	in stock

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità
The technical data here reported have been measured at 23°C with 50% humidity



Spirale in PVC rigido antiurto
Anti-shock rigid PVC spiral



Tubo in PVC-P
PVC-P hose

JP = Just pick, in stock

