


ES Tubo transparente de PVC-P, con espiral de refuerzo de PVC-P rígido antichoque de color marfil. Totalmente liso interiormente, ligero y muy flexible. Resistente a cargas, a los agentes atmosféricos y a muchos productos químicos. Versión antiestática con hilo de cobre disponible bajo pedido (Cod. NQ 02). Para uso alimentario según la normativa UE 10/2011 (clases A, B, C, D1); indicado para el transporte de leche y derivados en el sector lácteo.

• Solución ideal para aspiración y impulsión de polvos alimentarios, cereales, alimentos liofilizados, bebidas, zumos de frutas, vinagre, vino y licores con una concentración alcohólica de hasta el 50%. En agricultura, se utiliza en camiones cisterna y vehículos esparcidores de fertilizantes líquidos.

EN Transparent PVC-P hose, reinforced with an ivory anti-shock rigid PVC spiral. Smooth inside, light and very flexible. Resistant to loads, weathering and to a wide range of chemicals. The AS version with copper wire is available on request (Cod. NQ 02). Food grade, according to EU 10/2011 (classes A, B, C, D1) and suitable for passage of milk and dairy products.

• Ideal solution for suction and delivery of food powders flours, light grains, freeze dried foodstuffs as well as for liquid in general, beverage, juices, milk and by-products, vinegar, wines and liquours with an alcohol content up to 50%. In agriculture, used on tank trucks and manure spreaders.

ARTÍCULOS DE LA MISMA SERIE • ITEMS IN THE SAME SERIES



NETTUNO SE



BACCO



NETTUNO ENO

FICHA TÉCNICA • TECHNICAL DATA

NETTUNO	ø int.		Espesor mín Min wall thick	Espesor max max wall thick	Peso Weight	P.T. W.P.	P.R. B.P.	Vacio Vacuum	R. de curvatura Bending r.	Lg. Rollo Coil lgth.	Volume	Disponibilidad Availability
CÓDIGO/CODE	mm	inches	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³	
NQ010130000000	13		2,4	3,1	160	10	30	7	75	50	0,035	✓
NQ010160000000	16		2,5	3,2	200	8	24	7	90	50	0,040	✓
NQ010190000000*	19,1		2,6	3,3	240	7	21	7	110	50	0,056	bajo pedido/on request*
NQ010200000000	20		2,6	3,3	250	7	21	7	110	50	0,057	en stock
NQ010220000000*	22		2,6	3,3	270	7	20	7	110	50	0,062	bajo pedido/on request*
NQ010250000000	25		2,6	3,3	300	6	18	7	130	50	0,080	en stock
NQ010300000000	30		2,7	3,4	370	5	15	7	150	50	0,118	en stock
NQ010320000000	31,8		2,7	3,4	390	5	15	7	155	50	0,124	en stock
NQ010350000000	35		2,7	3,8	460	4	12	7	170	50	0,136	✓
NQ010380000000	38,1	1 1/2	2,9	4	530	4	12	7	180	50	0,148	en stock
NQ010390000000*	39		2,9	4	540	4	12	7	190	50	0,180	bajo pedido/on request*
NQ010400000000	40		3	4,1	580	4	12	7	195	50	0,185	en stock
NQ010450000000	45		3,2	4,4	700	4	12	7	215	50	0,241	✓
NQ010500000000	50		3,3	4,8	840	4	12	7	235	50	0,343	en stock
NQ010515000000*	51,5		3,3	4,8	860	4	12	7	245	50	0,352	bajo pedido/on request*
NQ010520000000	50,8	2	3,3	4,8	850	4	12	7	235	50	0,348	✓
NQ010550000000*	55		3,4	4,9	940	4	12	7	255	50	0,373	bajo pedido/on request*
NQ010570000000*	57		3,4	4,9	970	4	12	7	265	50	0,385	bajo pedido/on request*
NQ010600000000	60		3,4	4,9	1020	4	12	7	275	50	0,402	en stock
NQ010630000000	63,5	2 1/2	3,4	5	1100	4	12	7	290	50	0,423	en stock
NQ010650000000*	65		3,5	5,1	1160	4	12	7	300	50	0,433	bajo pedido/on request*
NQ010700000000	70		3,7	5,3	1260	3	9	7	320	50	0,580	en stock
NQ010750000000*	75		3,9	5,5	1420	3	9	7	340	50	0,619	bajo pedido/on request*
NQ010760000000	76,2	3	3,9	5,5	1440	3	9	7	340	50	0,628	en stock
NQ010777000000*	77,7		3,9	5,5	1470	3	9	7	350	50	0,639	bajo pedido/on request*
NQ010800000000	80		4,2	5,8	1590	3	9	7	365	50	0,660	en stock
NQ010900000000	90		4,4	6,2	1920	3	9	7	420	30	0,737	✓
NQ011000000000	100		4,8	6,7	2290	3	9	7	470	30	0,871	en stock
NQ011020000000	102		4,8	6,7	2340	3	9	7	470	30	0,886	✓
NQ011035000000*	103,5		4,9	6,8	2420	3	9	7	490	30	0,899	bajo pedido/on request*
NQ011050000000*	105		4,9	6,8	2450	3	9	7	490	30	0,911	bajo pedido/on request*
NQ011100000000*	110		5	7	2620	3	9	6	520	30	0,952	bajo pedido/on request*
NQ011200000000*	120		5,1	7,1	2910	3	9	6	650	30	1,031	bajo pedido/on request*
NQ011270000000*	127	5	5,2	7,2	3130	3	9	5,5	680	30	1,131	bajo pedido/on request*
NQ011300000000*	130		5,3	7,5	3340	3	9	5	700	30	1,160	bajo pedido/on request*
NQ011400000000*	140		5,7	8	3900	3	9	5	750	20	1,248	bajo pedido/on request*
NQ011500000000*	151,5		6,1	8,5	4480	3	9	5	780	20	1,348	bajo pedido/on request*
NQ011520000000*	152,8		6,1	8,5	4510	3	9	5	780	20	1,358	bajo pedido/on request*
NQ011600000000*	160		6,3	9,1	4860	2	6	4,5	850	20	1,426	bajo pedido/on request*
NQ012000000000*	200		6,5	10,3	6640	2	6	4,5	1000	10	2,135	bajo pedido/on request*
NQ012030000000*	203,2	8	6,5	10,3	6740	2	6	4,5	1000	10	2,166	bajo pedido/on request*
NQ012500000000*	250		6,8	10,8	8750	1,5	4,5	4	1800	Tramo 10 m/straight	0,738	bajo pedido/on request*
NQ012540000000*	254	10	6,8	10,8	8890	1,5	4,5	4	1800	Tramo 10 m/straight	0,760	bajo pedido/on request*
NQ013000000000*	300		7,2	11,4	11220	1	3	4	2000	Tramo 10 m/straight	1,042	bajo pedido/on request*
NQ013050000000*	304,8	12	7,2	11,4	11400	1	3	4	2000	Tramo 10 m/straight	1,073	bajo pedido/on request*

* Diámetros bajo pedido para cantidades mínimas (MOQ), según disponibilidad en almacén • * Diameters available on request for minimum order quantities (MOQ), unless in stock

Versión AS JP/AS version	ø int.		Espesor mín Min wall thick	Espesor max max wall thick	Peso Weight	P.T. W.P.	P.R. B.P.	Vacio Vacuum	R. de curvatura Bending r.	Lg. Rollo Coil lgth.	Volume	Disponibilidad Availability
	mm	inches	mm	mm	g/m	bar	bar	m H ₂ O	mm	m	m ³	
NQ020500000000	50		3,3	4,50	870	4	12	7	235	50	0,255	en stock

NETTUNO

CÓD. NQ 01 • Ø mm 13-305



Espiral de PVC rígido antichoque
Anti-shock rigid PVC spiral



Tubo de PVC-P
PVC-P hose

JP = Just pick, en stock

